

# CMF5529K800BER6

## CMF5529K800BER6 Information

www.tills.mr.com	Part Number	CMF5529K800BER6	
	Manufacturer	Vishay Dale	ലംഗം
	Category	Resistors Through Hole Resistors	
	Description	RES 29.8K OHM 1/2W 0.1% AXIAL	- <b>266</b> 87
	Package	Axial	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



a Quote

# CMF5529K800BER6 Specifications

Manufacturer Part Number CMF5529K800BER6   Manufacturer Vishay Dale   Category Resistors   Through Hole Resistors Through Hole Resistors   Package Axial   Series CMF   Resistance 9.8 KOhms   Tolerance ±0.1%   Power (Watts) 0.5W, 1/2W   Composition Metal Film   Features Flame Retardant Coating, Moisture Resistant, Safety   Operating Temperature ±55pm/°C   Operating Temperature 55°C ~ 175°C   Package / Case Axial   Supplier Device Package Axial   Size / Dimension 0.090° Dia x 0.240° L (2.29mm x 6.10mm)   Height - Seated (Max) -   Number of Terminations 2   Faiture Rate -			
CategoryResistorsPackageAxialPackageAxialSeriesCMFResistance29.8 kOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFame Retardant Coating, Moisture Resistant, SafetyTolperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSize / Dimension0.090° Dia x 0.240° L (2.29mm x 6.10mm)Height - Seated (Max)2Number of Terminations2Failure Rate-Failure Rate <td>Manufacturer Part Number</td> <td colspan="2">CMF5529K800BER6</td>	Manufacturer Part Number	CMF5529K800BER6	
Through Hole ResistorsPackageAxialSeriesCMFResistance9.8 kOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090° Dia x 0.240° L (2.29mm x 6.10mm)Height - Seated (Max)2Sunber of Terminations2Failure Rate-Failure Rate	Manufacturer	Vishay Dale	
PackageAxiaSeriesCMFResistance29.8 kOhmsTolerance±0.1%Power (Wats)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature±25ppm/°CPackage / CaseAxialSupplier Device Package0.900° Dia x 0.240° L (2.29mm x 6.10mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-Failure Rate- <t< td=""><td>Category</td><td colspan="2">Resistors</td></t<>	Category	Resistors	
SeriesCMFResistance29.8 kOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-Failure Rate-		Through Hole Resistors	
Resistance29.8 kOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°COperating TemperatureAxialSupplier Device Package0.090° Dia x 0.240° L (2.29mm x 6.10mm)Height - Seated (Max)-Aumber of Terminations2Failure Rate-Failure Rate-State Safet Safe	Package	Axial	
Tolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Aumber of Terminations2Failure Rate-Other Seated (Max)-State Seated (Max)-	Series	CMF	
Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Resistance	29.8 kOhms	
CompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Tolerance	±0.1%	
FeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Power (Watts)	0.5W, 1/2W	
Temperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Composition	Metal Film	
Operating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Features	Flame Retardant Coating, Moisture Resistant, Safety	
Package / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Temperature Coefficient	±25ppm/°C	
Supplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 175°C	
Number of Terminations0.090" Dia x 0.240" L (2.29mm x 6.10mm)Failure Rate-Autor of Terminations-Construc	Package / Case	Axial	
Height - Seated (Max)-Number of Terminations2Failure Rate-	Supplier Device Package	Axial	
Number of Terminations2Failure Rate-	Size / Dimension	0.090" Dia x 0.240" L (2.29mm x 6.10mm)	
Failure Rate -	Height - Seated (Max)	-	
	Number of Terminations	2	
Report errors?	Failure Rate	-	
		Report errors?	

### CMF5529K800BER6 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### CMF5529K800BER6 Payment Methods



If you have any question about CMF5529K800BER6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com