

# CMF553M0100FHRE

#### **CMF553M0100FHRE Information**

	Part Number	CMF553M0100FHRE	
	Manufacturer	Vishay Dale	fails that
www.trailernyr.com	Category	Resistors Through Hole Resistors	
	Description	RES 3.01M OHM 1/2W 1% AXIAL	- X-24
	Package	Axial	
		For the pricing/inventory/lead time, please contact us	(E19645
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a
		Manufacturer Category Description Package	WWW Comparison Through Hole Resistors   Description RES 3.01M OHM 1/2W 1% AXIAL   Package Axial   For Reference Only For the pricing/inventory/lead time, please contact us   Website: https://www.heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Quote

### **CMF553M0100FHRE Specifications**

Manufacturer Part NumberCMF553M0100FHREManufacturerVishay DaleCategoryResistorsThrough Hole ResistorsThrough Hole ResistorsPackageAxialSeriesCMFResistance3.01 MOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient-55°C ~ 175°CPackage / CaseAxial
CategoryResistorsCategoryResistorsThrough Hole ResistorsPackageAxialSeriesCMFResistance3.01 MOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 175°C
Through Hole ResistorsPackageAxialSeriesCMFResistance3.01 MOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 175°C
PackageAxialSeriesCMFResistance3.01 MOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°C
SeriesCMFResistance3.01 MOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°C
Resistance3.01 MOhmsTolerance±1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°C
Tolerance±1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°C
Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°C
CompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°C
FeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°C
Temperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°C
Operating Temperature $-55^{\circ}C \sim 175^{\circ}C$
Package / Case Axial
Supplier Device Package Axial
Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)
Height - Seated (Max) -
Number of Terminations 2
Failure Rate -
Report error

#### **CMF553M0100FHRE** Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **CMF553M0100FHRE Payment Methods**



If you have any question about CMF553M0100FHRE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com