

CMF6016K200FHBF

CMF6016K200FHBF Information

| | Part Number | CMF6016K200FHBF | |
|--------------------|--------------|---|--------------|
| | Manufacturer | Vishay Dale | 国际 中的 |
| www.sialberry.com | Category | Resistors Through Hole Resistors | |
| | Description | RES 16.2K OHM 1W 1% AXIAL | - 1924 |
| | Package | Axial | |
| | | For the pricing/inventory/lead time, please contact us | (E1%#9 |
| For Reference Only | | Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a |
| | | | |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Quote

CMF6016K200FHBF Specifications

| Manufacturer Part NumberCMF6016K200FHBFManufacturerVishay DaleCategoryResistorsCategoryThrough Hole ResistorsPackageAxialSeriesCMFResistance16.2 kOhmsTolerance±1%Power (Watts)IWCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient-55°C ~ 175°C |
|---|
| CategoryResistorsThrough Hole ResistorsPackageAxialSeriesCMFResistance16.2 kOhmsTolerance±1%Power (Watts)IWCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C |
| Through Hole ResistorsPackageAxialSeriesCMFResistance16.2 kOhmsTolerance±1%Power (Watts)IWCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C |
| PackageAxialSeriesCMFResistance16.2 kOhmsTolerance±1%Power (Watts)IWCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50pm/°C |
| SeriesCMFResistance16.2 kOhmsTolerance±1%Power (Watts)IWCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C |
| Resistance16.2 kOhmsTolerance±1%Power (Watts)1WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50pm/°C |
| Tolerance±1%Power (Watts)IWCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50pm/°C |
| Power (Watts)IWCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50pm/°C |
| CompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C |
| FeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C |
| Temperature Coefficient ±50ppm/°C |
| |
| Operating Temperature -55° C $\sim 175^{\circ}$ C |
| operating reinperature -55 C ~ 175 C |
| Package / Case Axial |
| Supplier Device Package Axial |
| Size / Dimension 0.145" Dia x 0.344" L (3.68mm x 8.74mm) |
| Height - Seated (Max) - |
| Number of Terminations 2 |
| Failure Rate - |
| Report error |

CMF6016K200FHBF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CMF6016K200FHBF Payment Methods



If you have any question about CMF6016K200FHBF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com