

CMF70120K00JKBF

CMF70120K00JKBF Information

Heisener.com	Part Number	CMF70120K00JKBF	
	Manufacturer	Vishay Dale	Tell 1750
	Category	Resistors Through Hole Resistors	
	Description	RES 120K OHM 1.75W 5% AXIAL	- 32
	Package	Axial	一音歌
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



a Quote

CMF70120K00JKBF Specifications

Manufacturer Part NumberCMF70120K00JKBFManufacturerVishay DaleCategoryResistorsThrough Hole ResistorsPackageAxialSeriesCMFResistance120 kOhmsTolerance±5%Power (Watts)1.75WCompositionMetal FilmFeaturesFalme Retardant Coating, Moisture Resistant, SafetyPoperature Coefficient±00pm/°COperating TemperatureAxialSupplier Device PackageAxialSize / Dimension0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)2Falure Reter-Falure Reter-Falure Reter-Size / Dimension2Size / Dimension-Size / Dimension </th <th></th> <th></th>		
CategoryResistorsPackageAxialPackageCMFResistance120 kOhmsTolerance±5%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature-55°C ~ 175°CPackage / CaseAxialSize / Dimension0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)-Anial-Stare Retardant Coating And SafetySize / Dimension0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)-Suppler Derice Retardant-Stare Retardant Coating And SafetyHeight - Seated (Max)-Stare Retardant Coating And SafetyStare Retardant Coating And SafetyStare Retardant Coating And SafetyStare Retardant Coating And SafetyStare Dimension-Stare Dimension-Stare Retardant Coating And SafetyStare Retardant Coating And SafetyStare Retardant Coating And SafetyStare Dimension-Stare Dimension-Stare Retardant Coating And SafetyStare Retardant Retardant Retardant Retardant Retardant Retardant Retardant Retardant	Manufacturer Part Number	CMF70120K00JKBF
Through Hole ResistorsPackageAxialSeriesCMFResistance120 kOhmsTolerance±5%Power (Wats)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180° Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)2Failure Rate-	Manufacturer	Vishay Dale
PackageAxiaSeriesCMFResistance120 kOhmsTolerance±5%Power (Wats)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature±5°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)2Failure Rate-Failure Rate2	Category	Resistors
SeriesCMFResistance120 kOhmsTolerance±5%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature±100ppm/°COperating TemperatureAxialSupplier Device PackageAxialSize / Dimension0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)2Failure Rate-Failure Rate-		Through Hole Resistors
Resistance120 kOhmsTolerance±5%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.180° Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Aumber of Terminations2Failure Rate-Stafe Composition-Stafe Composition <td>Package</td> <td>Axial</td>	Package	Axial
Tolerance±5%Power (Watts)1.75WCompositionMetal FilmFeaturesFame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-Other Seated (Max)-State Seated (Max)-	Series	CMF
Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180° Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Failure Rate1.	Resistance	120 kOhms
CompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Tolerance	$\pm 5\%$
FeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Power (Watts)	1.75W
Temperature Coefficient±100ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Composition	Metal Film
Operating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Features	Flame Retardant Coating, Moisture Resistant, Safety
Package / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Temperature Coefficient	±100ppm/°C
Supplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 175°C
Number of Terminations0.180" Dia x 0.562" L (4.57mm x 14.27mm)Failure Rate-Output-State (Max)-State (Max)- <tr< td=""><td>Package / Case</td><td>Axial</td></tr<>	Package / Case	Axial
Height - Seated (Max)-Number of Terminations2Failure Rate-	Supplier Device Package	Axial
Number of Terminations2Failure Rate-	Size / Dimension	0.180" Dia x 0.562" L (4.57mm x 14.27mm)
Failure Rate -	Height - Seated (Max)	-
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

CMF70120K00JKBF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CMF70120K00JKBF Payment Methods



If you have any question about CMF70120K00JKBF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com