

CMF7027R400FKR6

CMF7027R400FKR6 Information

For Reference Only	Part Number	CMF7027R400FKR6	
	Manufacturer	Vishay Dale	61 52
	Category	Resistors Through Hole Resistors	
	Description	RES 27.4 OHM 1.75W 1% AXIAL	- 9 <u>2</u> 4
	Package	Axial	
		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



a Quote

CMF7027R400FKR6 Specifications

Manufacturer Part Number CMF7027R400FKR6 Manufacturer Vishay Dale Category Resistors Through Hole Resistors Through Hole Resistors Package Axial Series CMF7 Resistance 27.4 Ohms Tolerance ±1% Power (Watts) 1.75W Composition Metal Film Features Flame Retardant Coating, Moisture Resistant, Safety Poperafure Coefficient ±100pm/°C Operating Temperature -55°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.180° Dia x 0.562° L (4.57mm x 14.27mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -			
CategoryResCategoryThrough Hole ResistorsPackageAxialPackageCMFResistance27.4 OhmsTolerance±1%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100pm/°COperating TemperatureAxialSupplier Device PackageAxialSize / Dimension0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-Failure Rate-Failur	Manufacturer Part Number	CMF7027R400FKR6	
Through Hole ResistorsPackageAxialSeriesCMFResistance27.4 OhmsTolerance±1%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180° Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)2Failure Rate-	Manufacturer	Vishay Dale	
PackageAxiaSeriesCMFResistance27.4 OhmsTolerance±1%Power (Wats)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature±100ppm/°COperating TemperatureAxialSupplier Device PackageAxialSize / Dimension0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)2Anumber of Terminations2Failure Rate-	Category	Resistors	
SeriesCMFResistance27.4 OhmsTolerance±1%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-		Through Hole Resistors	
Resistance27.4 OhmsTolerance±1%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.180° Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Aumber of Terminations2Failure Rate-Failure Rate-Failure Rate-	Package	Axial	
Tolerance±1%Power (Watts)1.75WCompositionMetal FilmFeaturesFame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-Other Seated (Max)-Suppler Device Package-Suppler Device Package-Start Of Terminations-Suppler Device Package-Start Of Terminations-Suppler Device Package-Start Of Terminations-Start Of Terminations- <trt< td=""><td>Series</td><td>CMF</td></trt<>	Series	CMF	
Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)-Failure Rate2	Resistance	27.4 Ohms	
CompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Tolerance	$\pm 1\%$	
FeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Power (Watts)	1.75W	
Temperature Coefficient±100ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Composition	Metal Film	
Operating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Features	Flame Retardant Coating, Moisture Resistant, Safety	
Package / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Temperature Coefficient	±100ppm/°C	
Supplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 175°C	
Number of Terminations0.180" Dia x 0.562" L (4.57mm x 14.27mm)Failure Rate-Output-State (Max)-State (Max)- <tr< td=""><td>Package / Case</td><td>Axial</td></tr<>	Package / Case	Axial	
Height - Seated (Max)-Number of Terminations2Failure Rate-	Supplier Device Package	Axial	
Number of Terminations2Failure Rate-	Size / Dimension	0.180" Dia x 0.562" L (4.57mm x 14.27mm)	
Failure Rate -	Height - Seated (Max)	-	
	Number of Terminations	2	
Report errors?	Failure Rate	-	
		Report errors?	

CMF7027R400FKR6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CMF7027R400FKR6 Payment Methods



If you have any question about CMF7027R400FKR6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com