

# CMF702M1400FHRE

## **CMF702M1400FHRE Information**

(A Heisener.com	Part Number	CMF702M1400FHRE	
	Manufacturer	Vishay Dale	Tell 171
	Category	Resistors Through Hole Resistors	
COMPANY CONTRACTOR	Description	RES 2.14M OHM 1.75W 1% AXIAL	- 82
	Package	Axial	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com	D
I of Reference Only		E-mail: salesdept@heisener.com	Request

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



a Quote

# **CMF702M1400FHRE Specifications**

ManufacturerVishay DaleCategoryResistorsThrough Hole ResistorsPackageAxialSeriesCMFResistance.14 MOhmsTolerance±1%Power (Watts).75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyPower Quer Series.55°C ~ 175°COperating Temperature.55°C ~ 175°CPackage / CaseAxialSupplier Device Package.180° Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max).Failure Rate.Failure Rate <th></th> <th></th>		
CategoryResistorsPackageAxialPackageCMFResistance2.14 MOhmsTolerance±1%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature-55°C ~ 175°CPackage / CaseAxialSize / Dimension0.180° Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Failure Rate-Failure Rate-Failur	Manufacturer Part Number	CMF702M1400FHRE
Through Hole ResistorsPackageAxialPackageCMFResistance2.14 MOhmsTolerance±1%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyPoperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)2Failure Rate-Failure Rate- <t< td=""><td>Manufacturer</td><td>Vishay Dale</td></t<>	Manufacturer	Vishay Dale
PackageAxialSeriesCMFResistance2.14 MOhmsTolerance±1%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.180° Dia x 0.562° L (4.57mm x 14.27mm)Height - Seated (Max)-Failure Rate-Failure Rate-Failure Rate-	Category	Resistors
Series     CMF       Resistance     2.14 MOhms       Tolerance     ±1%       Power (Watts)     1.75W       Composition     Metal Film       Features     Flame Retardant Coating, Moisture Resistant, Safety       Poper (Yatts)     -55°C ~ 175°C       Opprating Temperature     Axial       Supplier Device Package     Axial       Supplier Device Package     0.180° Dia x 0.562° L (4.57mm x 14.27mm)       Height - Seated (Max)     2       Failure Rate     -		Through Hole Resistors
Resistance2.14 MOhmsTolerance±1%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Aumber of Terminations2Failure Rate-	Package	Axial
Tolerance±1%Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Series	CMF
Power (Watts)1.75WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Resistance	2.14 MOhms
CompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Tolerance	$\pm 1\%$
FeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Power (Watts)	1.75W
Temperature Coefficient±50ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Composition	Metal Film
Operating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Features	Flame Retardant Coating, Moisture Resistant, Safety
Package / CaseAxialSupplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Temperature Coefficient	±50ppm/°C
Supplier Device PackageAxialSize / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 175°C
Size / Dimension0.180" Dia x 0.562" L (4.57mm x 14.27mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Package / Case	Axial
Height - Seated (Max)-Number of Terminations2Failure Rate-	Supplier Device Package	Axial
Number of Terminations 2   Failure Rate -	Size / Dimension	0.180" Dia x 0.562" L (4.57mm x 14.27mm)
Failure Rate -	Height - Seated (Max)	-
	Number of Terminations	2
Report errors?	Failure Rate	-
1		Report errors?

## **CMF702M1400FHRE** Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CMF702M1400FHRE Payment Methods**



If you have any question about CMF702M1400FHRE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com