

CN0966A14A12P8-200

CN0966A14A12P8-200 Information

| Contact levels cards here | CN0966A14A12P8-200 Cinch Connectivity Solutions Connectors, Interconnects Circular Connectors CONN PLUG MALE 12POS GOLD CRIMP - For the pricing/inventory/lead time, please contact | |
|---------------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CN0966A14A12P8-200 Specifications

| Manufacturer Part Number CN0966A14A12P8-200 Manufacturer Cinch Connectivity Solutions Category Connectors, Interconnects Package - Package - Series MIL-DTL-26500, CN0966 Connector Type Plug, Male Pins Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation S Shell Material, Finish Aluminum, Anodized Contact Finish Self Locking, Shielded Voltage - Rated - Voltage - Rated - | | |
|---|--------------------------|------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26500, CN0966Connector TypePlug, Male PinsConnector Type12Number of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpGrientation8Ingress ProtectionSulvionment SealedShell Material, FinishGoldContact FinishSelf Locking, ShieldedVoltage - Rated-Cortent RatingSelf Locking, ShieldedForter Rating-Solage - Rated-Cortert Rating-Solage - Rated-Cortert Rating-Solage - Rated-Solage - Rated-Cortert Rating-Solage - Rated-Cortert Rating-Solage - Rated-Solage - Ratering - Solage - Solage - Solage - Solage - Solage - Solage - Sola | Manufacturer Part Number | CN0966A14A12P8-200 |
| AckageCircular ConnectorsPackage-SeriesMIL-DTL-26500, CN0966Connector TypePlug, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientation8Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishSelf Locking, ShieldedYoltage - Rated-Current Rating-Current Rating-Current Rating- | Manufacturer | Cinch Connectivity Solutions |
| Package-SeriesMIL-DTL-26500, CN0966Connector TypePlug, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientation8Shell Material, FinishAluminum, AnodizedShell Material, FinishSelf Locking, ShieldedFotaresSelf Locking, ShieldedFotaresSelf Locking, ShieldedFotares-Current Rating-Current Rating-State Material, FinishSelf Locking, ShieldedFotaresSelf Locking, ShieldedFotares-State Material Finish-State Material FinishSelf Locking, ShieldedFotaresSelf Locking, ShieldedFotares-State Material Finish-State Material Finish-State Material Finish-State Material FinishSelf Locking, ShieldedFotares-State Material Finish-State Material Finish-State Material Finish-State Material FinishSelf Locking, ShieldedFinishState Material Finish-State Material Finish-State Material Finish-State Material Finish-State Material Finish-State Material Finish-St | Category | Connectors, Interconnects |
| SeriesMIL-DTL-26500, CN0966Connector TypePlug, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientation8Ingress ProtectionEnvironment SealedShell Material, FinishGoldContact FinishSelf Locking, ShieldedVoltage - Rated-Corrent Rating-Corrent Rating | | Circular Connectors |
| Connector TypePlug, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeHreadedOrientation8Ingress ProtectionAuminum, AnodizedShell Material, FinishGoldFoaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-Current Rating-< | Package | - |
| Number of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientation8Ingress ProtectionEnvironment SealedShell Material, FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-Current Rating-Shell Material, Shielded-StatementSelf Locking, ShieldedStatement- <td>Series</td> <td>MIL-DTL-26500, CN0966</td> | Series | MIL-DTL-26500, CN0966 |
| Shell Size - Insert14-12Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientation8Ingress ProtectionEnvironment SealedShell Material, FinishGoldContact FinishSelf Locking, ShieldedFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-Current Rating- | Connector Type | Plug, Male Pins |
| Shell Size, MIL-Mouning TypeFree Hanging (In-Line)TerminationCrimpFastening TypeMineadedOrientation8Ingress ProtectionEnvironment SealedShell Material, FinishGoldContact FinishSelf Locking, ShieldedFeaturesSelf Locking, ShieldedVoltage - Rating-Current Rating-Cur | Number of Positions | 12 |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientation8Ingress ProtectionEnvironment SealedShell Material, FinishGoldContact FinishSelf Locking, ShieldedFeatures-Voltage - Rated-Current Rating-Current Rating-Current Rating- | Shell Size - Insert | 14-12 |
| TerminationCrimpFastening TypeThreadedOrientation8Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating- | Shell Size, MIL | - |
| Fastening TypeThreadedFastening TypeNreadedOrientation8Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating- | Mounting Type | Free Hanging (In-Line) |
| Orientation8Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating- | Termination | Crimp |
| Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating6 | Fastening Type | Threaded |
| Shell Material, FinishAluminum, AnodizedContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating- | Orientation | 8 |
| Contact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating- | Ingress Protection | Environment Sealed |
| FeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-Output-Current Rating-Current Rating-Curren | Shell Material, Finish | Aluminum, Anodized |
| Voltage - Rated-Current Rating- | Contact Finish | Gold |
| Current Rating - | Features | Self Locking, Shielded |
| - | Voltage - Rated | - |
| Report errors? | Current Rating | - |
| | | Report errors? |

CN0966A14A12P8-200 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CN0966A14A12P8-200 Payment Methods



If you have any question about CN0966A14A12P8-200, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com