

CN0966B24S43SNY140

CN0966B24S43SNY140 Information

Heisener.com	 CN0966B24S43SNY140 Cinch Connectivity Solutions Connectors, Interconnects Circular Connectors CONN PLUG FMALE 43POS GOLD CRIMP - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CN0966B24S43SNY140 Specifications

Manufacturer Part Number CN0966B24S43SNY140 Manufacturer Cinch Connectivity Solutions Category Connectors, Interconnects Category Circular Connectors Package - Series MIL-DTL-26500, CN0966 Connector Type Plug, Female Sockets Number of Positions 43 Shell Size - Insert 24:43 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Afference N(Normal) Ingress Protection Stailess Steel Contact Finish Gold Voltage - Rated - Voltage - Rated -		
CategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesMIL-DTL-26500, CN0966Connector TypePlug, Female SocketsNumber of Positions43Shell Size - Insert24-43Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionStailless SteelShell Material, FinishStailless SteelContact FinishSelf Locking, ShieldedFeaturesSelf Locking, ShieldedYoltage - Rated-Current Rating-Current Rating-Current Rating-Current Rating-	Manufacturer Part Number	CN0966B24S43SNY140
Initial ConnectorsPackage-SeriesMIL-DTL-26500, CN0966Connector TypePlug, Fenale SocketsNumber of Positions43Shell Size - Insert24-43Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment SealedShell Material, FinishStainless SteelContact FinishSelf Locking, ShieldedVoltage - Rated-Current Rating-Current	Manufacturer	Cinch Connectivity Solutions
Package.SeriesMIL-DTL-26500, CN0966Connector TypePlug, Female SocketsNumber of Positions43Shell Size - Insert24-43Shell Size, MILFree Hanging (In-Line)Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeNI Normal)OrientationNi Normal)Shell Material, FinishStailess SteelConter FinishGoldFeaturesSelf Locking, SheldedVoltage - Rated.Current Rating.Current Rating.State Steel.Stell Rated.Stell Rated <td>Category</td> <td>Connectors, Interconnects</td>	Category	Connectors, Interconnects
SeriesMIL-DTL-26500, CN0966Connector TypePlug, Female SocketsNumber of Positions43Shell Size - Insert24-43Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment SealedShell Material, FinishGoldContact FinishSelf Locking, ShieldedFeaturesSelf Locking, ShieldedYoltage - Rateing-Corrent Rating-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions43Shell Size - Insert24-43Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeMormal/OrientationN (Normal)Ingress ProtectionStailess SteelShell Material, FinishGoldFoaturesStefl Locking, ShieldedVoltage - Rated-Current Rating-StantesStailess SteelStailes RatedSterl ShieldedStaturesStailes SteelStaturesSterl ShieldedStaturesStailes SteelStaturesSterl ShieldedStaturesStaturesStaturesSterl ShieldedStatures <t< td=""><td>Package</td><td>-</td></t<>	Package	-
Number of Positions43Shell Size - Insert24-43Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment SealedShell Material, FinishStainless SteelContact FinishSelf Locking, ShieldedVoltage - Rated-Current Rating-Current Rating-	Series	MIL-DTL-26500, CN0966
Shell Size - Insert24-43Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment SealedShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-	Connector Type	Plug, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeMreadedOrientationN(Normal)Ingress ProtectionEnvironment SealedShell Material, FinishSdialess SteelContact FinishSelf Locking, ShieldedFeaturesSelf Locking, ShieldedVoltage - Rating-Current Rating-Sterl Rating <td>Number of Positions</td> <td>43</td>	Number of Positions	43
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedFortantionN(Normal)OrientationEnvironment SealedShell Material, FinishSchales SteelContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-Stent	Shell Size - Insert	24-43
TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment SealedShell Material, FinishSdialess SteelContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-Sterent Seatures-Sterent Seatures- <t< td=""><td>Shell Size, MIL</td><td>-</td></t<>	Shell Size, MIL	-
Fastening TypeThreadedForientationN (Normal)Ingress ProtectionEnvironment SealedShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress ProtectionEnvironment SealedShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-	Termination	Crimp
Ingress ProtectionEnvironment SealedShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating6	Fastening Type	Threaded
SolutionStainless SteelShell Material, FinishStainless SteelContact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-	Orientation	N (Normal)
Contact FinishGoldFeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-	Ingress Protection	Environment Sealed
FeaturesSelf Locking, ShieldedVoltage - Rated-Current Rating-Output-Current Rating-Current Rating-Curren	Shell Material, Finish	Stainless Steel
Voltage - Rated-Current Rating-	Contact Finish	Gold
Current Rating -	Features	Self Locking, Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	-
		Report errors?

CN0966B24S43SNY140 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

CN0966B24S43SNY140 Payment Methods

CN0966B24S43SNY140 Shipping Methods



If you have any question about CN0966B24S43SNY140, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com