

CP10.242

CP10.242 Information



Part Number	CP10.242
Manufacturer	PULS, LP
Category	Power Supplies - External/Internal (Off-Board) AC DC Converters
Description	DIN RAIL PWR SUPPLY 240W 24V 10A
Package	-
	For the pricing/inventory/lead time, please contact us
	Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CP10.242 Specifications

Manufacturer Part NumberCP10.242ManufacturerPULS, LPCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesDIMENSION CPTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 30Voltage - Output 4-Power (Watts)10APower (Watts)240WApplicationsTIE (Commercial)Voltage Isolation3kV (300V)Efficiency95.2%Operating Temperature-Mounting TypeDIN RailMounting TypeDIN Rail		
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesDIMENSION CPTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Power (Watts)240WPower (Watts)10APower (Watts)3kV (3000V)Efficiency95.2%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeDIN Rail	Manufacturer Part Number	CP10.242
IdentifyAC DC ConvertersPackage-SeriesDIMENSION CPTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 410AVoltage - Output 410APower (Watts)240WApplicationsITE (Commercial)Voltage - Isolation3V (300V)Pertures9.5 %Operating Temperature-10°C ~ 70°C (With Derating)FeaturesDIN RailMounting Type5.1°L × 1.54° W x 4.88° H (117.0mm x 39.0mm x 124.0mm)	Manufacturer	PULS, LP
Package.SeriesDIMENSION CPTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2.Voltage - Output 3.Voltage - Output 4.Voltage - Output 4.Power (Watts).ApplicationsITE (Commercial)Voltage - Isolation.Poreating Temperature.Operating Temperature.Adjustabe Output, Apple.Features.Mounting Type.Siz / Dimension.Siz / Dimension.	Category	Power Supplies - External/Internal (Off-Board)
Series DIMENSION CP Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 - Voltage - Output 4 - Voltage - Output 4 - Voltage - Solation 10A Power (Wats) AV(3000V) Yoltage - Isolation StV (3000V) Efficiency 95.2% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 1		AC DC Converters
TypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Over (Wats)10APower (Wats)3KV (3000V)Voltage - Isolation3KV (3000V)Efficiency9.2%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustabe Output, DC Input, Capable, PFC, Universal Input,Nounting Type6.1°L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Voltage - Isolation TE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.2% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type JIN Rail	Series	DIMENSION CP
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.2% Operating Temperature Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Туре	Enclosed
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.2% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Number of Outputs	1
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10APower (Watts)240WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency95.2%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting Type0IN RailSize / Dimension4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Wats) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.2% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Voltage - Output 1	24V
Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.2% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Voltage - Output 2	-
Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.2% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Voltage - Output 3	-
Power (Watts)240WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency95.2%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency95.2%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Current - Output (Max)	10A
Voltage - Isolation3kV (3000V)Efficiency95.2%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Power (Watts)	240W
Efficiency95.2%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Applications	ITE (Commercial)
Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Voltage - Isolation	3kV (3000V)
FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Efficiency	95.2%
Mounting Type DIN Rail Size / Dimension 4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Operating Temperature	-10° C ~ 70° C (With Derating)
Size / Dimension 4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)	Features	Adjustable Output, DC Input Capable, PFC, Universal Input
	Mounting Type	DIN Rail
Descent	Size / Dimension	4.61" L x 1.54" W x 4.88" H (117.0mm x 39.0mm x 124.0mm)
Report		Report errors'

CP10.242 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about CP10.242, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com