

## CP1501-7R

## **CP1501-7R Information**

Heisener.com	Part Number Manufacturer Category Description Package	CP1501-7R Bel Power Solutions Power Supplies - External/Internal (Off-Board) DC DC Converters DC/DC CONVERT 15V 12.9A - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **CP1501-7R Specifications**

Manufacturer Part Number CP1501-7R   Manufacturer Bel Power Solutions   Category Power Supplies - External/Internal (Off-Board) DC DC Converters   Package -   Scries Melcher P   Type Isolated   Voltage - Input (Min) 33.6V   Voltage - Input (Max) 75V   Number of Outputs 1   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 5 -   Voltage - Output 6 -   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.9A   Power (Watts) 194W   Applications ITE (Commercial), Railway   Operating Temperature 25°C ~ 71°C   Efficiency 88.5%   Mounting Type Chassis Mount   Package / Case -				
CategoryPower Supplies - External/Internal (Off-Board)DC DC ConvertersPackage-SeriesMelcher PTypeIsolatedVoltage - Input (Min)33.6VVoltage - Input (Max)75VNumber of Outputs1Voltage - Output 151VVoltage - Output 151VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4194WPower (Watts)194WApplications15C Convertial (Max)Operating Temperature2:5° C ~ 1°CEfficiency88.5%Mounting Type-Package / Case-Siz / Dimension6:3" L x 4.3" W x 0.78" H (171.0mm x 110.mm x 19.8mm)	Manufacturer Part Number	CP1501-7R		
DC DC Converters   Package -   Series Melcher P   Type Isolated   Voltage - Input (Min) 33.6V   Voltage - Input (Max) 75V   Number of Outputs 1   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Operating Temperature -25°C ~ 71°C   Efficiency 88.5%   Mounting Type Chassis Mount   Package / Case -   Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Manufacturer	Bel Power Solutions		
Package.SeriesMelcher PTypeIsolatedVoltage Input (Min)33.6VVoltage Input (Max)75VNumber of Outputs1Voltage - Output 115VVoltage - Output 2.Voltage - Output 3.Voltage - Output 4.Voltage - Output 4.Power (Wats)194WApplications1FC (commercial), RailwayOperating Temperature.Strift Censer.5°C ~ 71°CEfficiencyStasi MountPackage / Case.Siz / Dimension.Siz / Dimension.<	Category	Power Supplies - External/Internal (Off-Board)		
SeriesMelcher PTypeIsolatedVoltage - Input (Min)33.6VVoltage - Input (Max)75VNumber of Outputs1Voltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12.9APover (Watts)194WApplicationsTE (Commercial), RailwayOperating Temperature85.5%Mounting Type-Package / Case-Siz / Dimension6.3" Lx 4.37" Wx 0.78" H (171.0mm x 191.8mm)		DC DC Converters		
TypeIsolatedYoltage Input (Min)33.6VVoltage Input (Max)75VNumber of Outputs1Voltage Output 115VVoltage Output 2-Voltage Output 3-Voltage Output 4-Voltage Output 412.9ACurrent Output (Max)194WApplications1TE (commercial), RailwayOperating Temperature85%Efficiency88.5%Mounting Type-Yoltage / Case-Size / Dimension6.73" L x 4.37" W x 0.78" H (171.0mm x 119.8mm)	Package	-		
Voltage - Input (Min) 33.6V   Voltage - Input (Max) 75V   Number of Outputs 1   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.9A   Power (Wats) 194W   Applications ITE (Commercial), Railway   Operating Temperature -25°C ~ 71°C   Efficiency 88.5%   Mounting Type Chasis Mount   Package / Case -   Size / Dinension 6.73" L x 4.37" W x 0.78" H (171.0mm x 19.8mm)	Series	Melcher P		
Voltage - Input (Max) 75V   Number of Outputs 1   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.9A   Power (Watts) 194W   Operating Temperature -25°C ~71°C   Efficiency 88.5%   Mounting Type Chasis Mount   Package / Case -   Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Туре	Isolated		
Number of Outputs 1   Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.9A   Power (Watts) 194W   Operating Temperature -25°C ~ 71°C   Efficiency 88.5%   Mounting Type Chassis Mount   Package / Case -   Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 119.8mm)	Voltage - Input (Min)	33.6V		
Voltage - Output 1 15V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.9A   Power (Watts) 194W   Applications ITE (Commercial), Railway   Operating Temperature -25°C ~ 71°C   Efficiency 88.5%   Mounting Type Chassis Mount   Package / Case -   Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Voltage - Input (Max)	75V		
Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.9A   Power (Watts) 194W   Applications TE (Commercial), Railway   Operating Temperature -25°C ~ 71°C   Efficiency 88.5%   Mounting Type Chassis Mount   Package / Case -   Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Number of Outputs	1		
Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.9A   Power (Watts) 194W   Applications ITE (Commercial), Railway   Operating Temperature -25°C ~ 71°C   Efficiency 88.5%   Mounting Type Chassis Mount   Package / Case -   Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Voltage - Output 1	15V		
Voltage - Output 4 -   Current - Output (Max) 12.9A   Power (Watts) 194W   Applications ITE (Commercial), Railway   Operating Temperature -25°C ~ 71°C   Efficiency 88.5%   Mounting Type Chassis Mount   Package / Case -   Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Voltage - Output 2	-		
Current - Output (Max)12.9APower (Watts)194WApplicationsITE (Commercial), RailwayOperating Temperature-25°C ~ 71°CEfficiency88.5%Mounting TypeChassis MountPackage / Case-Size / Dimension6.73" L x 4.37" W x 0.78" H (171.0mm x 119.8mm)	Voltage - Output 3	-		
Power (Watts)194WApplicationsITE (Commercial), RailwayOperating Temperature-25°C ~ 71°CEfficiency88.5%Mounting TypeChassis MountPackage / Case-Size / Dimension6.73" L x 4.37" W x 0.78" H (171.0mm x 19.8mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial), RailwayOperating Temperature-25°C ~ 71°CEfficiency88.5%Mounting TypeChassis MountPackage / Case-Size / Dimension6.73" L x 4.37" W x 0.78" H (171.0mm x 19.8mm)	Current - Output (Max)	12.9A		
Operating Temperature-25°C ~ 71°CEfficiency88.5%Mounting TypeChassis MountPackage / Case-Size / Dimension6.73" L x 4.37" W x 0.78" H (171.0mm x 19.8mm)	Power (Watts)	194W		
Efficiency88.5%Mounting TypeChassis MountPackage / Case-Size / Dimension6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Applications	ITE (Commercial), Railway		
Mounting TypeChassis MountPackage / Case-Size / Dimension $6.73"$ L x $4.37"$ W x $0.78"$ H ( $171.0mm$ x $111.0mm$ x $19.8mm$ )	Operating Temperature	-25°C ~ 71°C		
Package / Case -   Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Efficiency	88.5%		
Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Mounting Type	Chassis Mount		
	Package / Case	-		
Report errors	Size / Dimension	6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)		
			Report errors?	

#### **CP1501-7R Guarantees**



#### Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CP1501-7R Payment Methods**



### **CP1501-7R Shipping Methods**



If you have any question about CP1501-7R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com