

### **CP2540-7R Information**

Heisener.com

Part Number CP2540-7R

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

**Description** DC/DC CONVERT DUAL 15V 6.4A

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CP2540-7R Specifications**

Manufacturer Part Number         CP2540-7R           Manufacturer         Bel Power Solutions           Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         -           Series         Melcher P           Type         Isolated           Voltage - Input (Min)         33.6V           Voltage - Input (Max)         75V           Number of Outputs         2           Voltage - Output 1         15V           Voltage - Output 2         15V           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.4A, 6.4A           Power (Watts)         192W           Applications         ITE (Commercial), Railway           Operating Temperature         -25°C ~ 71°C           Efficiency         88.5%           Mounting Type         Chassis Mount           Package / Case         -           Size / Dimension         6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)           Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         -           Series         Melcher P           Type         Isolated           Voltage - Input (Min)         33.6V           Voltage - Input (Max)         75V           Number of Outputs         2           Voltage - Output 1         15V           Voltage - Output 2         15V           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.4A, 6.4A           Power (Watts)         192W           Applications         ITE (Commercial), Railway           Operating Temperature         -25°C ~ 71°C           Efficiency         88.5%           Mounting Type         Chassis Mount           Package / Case         -           Size / Dimension         6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Manufacturer Part Number	CP2540-7R
Package         -           Series         Melcher P           Type         Isolated           Voltage - Input (Min)         33.6V           Voltage - Input (Max)         75V           Number of Outputs         2           Voltage - Output 1         15V           Voltage - Output 2         15V           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.4A, 6.4A           Power (Watts)         192W           Applications         ITE (Commercial), Railway           Operating Temperature         -25°C ~ 71°C           Efficiency         88.5%           Mounting Type         Chassis Mount           Package / Case         -           Size / Dimension         6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Manufacturer	Bel Power Solutions
Package         -           Series         Melcher P           Type         Isolated           Voltage - Input (Min)         33.6V           Voltage - Input (Max)         75V           Number of Outputs         2           Voltage - Output 1         15V           Voltage - Output 2         15V           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.4A, 6.4A           Power (Watts)         192W           Applications         ITE (Commercial), Railway           Operating Temperature         -25°C ~ 71°C           Efficiency         88.5%           Mounting Type         Chassis Mount           Package / Case         -           Size / Dimension         6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         Melcher P           Type         Isolated           Voltage - Input (Min)         33.6V           Voltage - Input (Max)         75V           Number of Outputs         2           Voltage - Output 1         15V           Voltage - Output 2         15V           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.4A, 6.4A           Power (Watts)         192W           Applications         ITE (Commercial), Railway           Operating Temperature         -25°C ~ 71°C           Efficiency         88.5%           Mounting Type         Chassis Mount           Package / Case         -           Size / Dimension         6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)		DC DC Converters
Type         Isolated           Voltage - Input (Min)         33.6V           Voltage - Input (Max)         75V           Number of Outputs         2           Voltage - Output 1         15V           Voltage - Output 2         15V           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.4A, 6.4A           Power (Watts)         192W           Applications         ITE (Commercial), Railway           Operating Temperature         -25°C ~ 71°C           Efficiency         88.5%           Mounting Type         Chassis Mount           Package / Case         -           Size / Dimension         6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Package	-
Voltage - Input (Min)       33.6V         Voltage - Input (Max)       75V         Number of Outputs       2         Voltage - Output 1       15V         Voltage - Output 2       15V         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       6.4A, 6.4A         Power (Watts)       192W         Applications       ITE (Commercial), Railway         Operating Temperature       -25°C ~ 71°C         Efficiency       88.5%         Mounting Type       Chassis Mount         Package / Case       -         Size / Dimension       6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Series	Melcher P
Voltage - Input (Max)         75V           Number of Outputs         2           Voltage - Output 1         15V           Voltage - Output 2         15V           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.4A, 6.4A           Power (Watts)         192W           Applications         ITE (Commercial), Railway           Operating Temperature         -25°C ~ 71°C           Efficiency         88.5%           Mounting Type         Chassis Mount           Package / Case         -           Size / Dimension         6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Туре	Isolated
Number of Outputs       2         Voltage - Output 1       15V         Voltage - Output 2       15V         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       6.4A, 6.4A         Power (Watts)       192W         Applications       ITE (Commercial), Railway         Operating Temperature       -25°C ~ 71°C         Efficiency       88.5%         Mounting Type       Chassis Mount         Package / Case       -         Size / Dimension       6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Voltage - Input (Min)	33.6V
Voltage - Output 1       15V         Voltage - Output 2       15V         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       6.4A, 6.4A         Power (Watts)       192W         Applications       ITE (Commercial), Railway         Operating Temperature       -25°C ~ 71°C         Efficiency       88.5%         Mounting Type       Chassis Mount         Package / Case       -         Size / Dimension       6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Voltage - Input (Max)	75V
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature Efficiency 88.5% Mounting Type Chassis Mount Package / Case Size / Dimension  15V	Number of Outputs	2
Voltage - Output 4  Current - Output (Max)  Applications  Operating Temperature  Efficiency  Mounting Type  Size / Dimension  - Output 3  - Current - Output (Max)  6.4A, 6.4A  - Current - Output (Max)  6.4A, 6.4A  - Current - Output (Max)  192W  Applications  ITE (Commercial), Railway  - 25°C ~ 71°C  88.5%  Chassis Mount  - Chassis Mount	Voltage - Output 1	15V
Voltage - Output 4  Current - Output (Max) 6.4A, 6.4A  Power (Watts) 192W  Applications ITE (Commercial), Railway  Operating Temperature -25°C ~ 71°C  Efficiency 88.5%  Mounting Type Chassis Mount  Package / Case Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Voltage - Output 2	15V
Current - Output (Max) 6.4A, 6.4A  Power (Watts) 192W  Applications ITE (Commercial), Railway  Operating Temperature -25°C ~ 71°C  Efficiency 88.5%  Mounting Type Chassis Mount  Package / Case - Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial), Railway  Operating Temperature  -25°C ~ 71°C  Efficiency  88.5%  Mounting Type  Chassis Mount  Package / Case  Size / Dimension  192W  Commercial), Railway  -25°C ~ 71°C  Chasilway  -25°C ~ 71°C  Chasis Mount  102	Voltage - Output 4	-
Applications ITE (Commercial), Railway  Operating Temperature -25°C ~ 71°C  Efficiency 88.5%  Mounting Type Chassis Mount  Package / Case -  Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Current - Output (Max)	6.4A, 6.4A
Operating Temperature  -25°C ~ 71°C  Efficiency  88.5%  Mounting Type  Chassis Mount  Package / Case  -  Size / Dimension  -25°C ~ 71°C  -25°C	Power (Watts)	192W
Efficiency 88.5%  Mounting Type Chassis Mount  Package / Case -  Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Applications	ITE (Commercial), Railway
Mounting Type Chassis Mount  Package / Case - Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Operating Temperature	-25°C ~ 71°C
Package / Case - Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Efficiency	88.5%
Size / Dimension 6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)	Mounting Type	Chassis Mount
	Package / Case	-
Report errors?	Size / Dimension	6.73" L x 4.37" W x 0.78" H (171.0mm x 111.0mm x 19.8mm)
		Report errors?

#### CP2540-7R Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **CP2540-7R Payment Methods**





















### **CP2540-7R Shipping Methods**













If you have any question about CP2540-7R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com