



CPC30AFH Information

Heisener.com

Part Number CPC30AFH

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description ABS SIG CONDITION UNAMP

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CPC30AFH Specifications

Manufacturer Part Number CPC30AFH Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-SIP Module Series CPC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.15" (3.8mm) Tube Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 90 PSI (620.53 kPa) Operating Temperature -25°C ~ 85°C		
CategorySensors, TransducersPackage4-SIP ModuleSeriesCPCPressure TypeAbsoluteOperating Pressure30 PSI (206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 90 mV (12V)Accuracy±2%Voltage - Supply3 V ~ 16 VPort SizeMale - 0.15" (3.8mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination Style-Maximum Pressure90 PSI (620.53 kPa)Operating Temperature-25°C ~ 85°C	Manufacturer Part Number	CPC30AFH
Package 4-SIP Module Series CPC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output Type Wheatstone Bridge Output 4 2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.15" (3.8mm) Tube Port Style Barbed Features Temperature Compensated Termination Style Maximum Pressure 90 PSI (620.53 kPa) Operating Temperature - 25°C ~ 85°C	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-SIP Module Series CPC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.15" (3.8mm) Tube Port Style Barbed Features Temperature Compensated Termination Style Maximum Pressure 90 PSI (620.53 kPa) Operating Temperature	Category	Sensors, Transducers
Series CPC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.15" (3.8mm) Tube Port Style Barbed Features Temperature Compensated Termination Style Maximum Pressure 90 PSI (620.53 kPa) Operating Temperature -25°C ~ 85°C		Pressure Sensors, Transducers
Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.15" (3.8mm) Tube Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 90 PSI (620.53 kPa) Operating Temperature -25°C ~ 85°C	Package	4-SIP Module
Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.15" (3.8mm) Tube Port Style Features Temperature Compensated Termination Style	Series	CPC
Output Type	Pressure Type	Absolute
Output $0 \text{ mV} \sim 90 \text{ mV} (12\text{V})$ Accuracy $\pm 2\%$ Voltage - Supply $3 \text{ V} \sim 16 \text{ V}$ Port Size $\text{Male} - 0.15'' (3.8 \text{mm}) \text{ Tube}$ Port Style Barbed Features $\text{Temperature Compensated}$ Termination Style $-$ Maximum Pressure $90 \text{ PSI } (620.53 \text{ kPa})$ Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Operating Pressure	30 PSI (206.84 kPa)
Accuracy $\pm 2\%$ Voltage - Supply $3 \text{ V} \sim 16 \text{ V}$ Port SizeMale - 0.15 " (3.8mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination Style-Maximum Pressure $90 \text{ PSI } (620.53 \text{ kPa})$ Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Output Type	Wheatstone Bridge
Voltage - Supply $3 \text{ V} \sim 16 \text{ V}$ Port Size $\text{Male} - 0.15'' (3.8 \text{mm}) \text{ Tube}$ Port Style Barbed Features $\text{Temperature Compensated}$ Termination Style $-$ Maximum Pressure $90 \text{ PSI } (620.53 \text{ kPa})$ Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Output	$0 \text{ mV} \sim 90 \text{ mV} (12 \text{V})$
Port Size Male - 0.15" (3.8mm) Tube Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 90 PSI (620.53 kPa) Operating Temperature -25°C ~ 85°C	Accuracy	±2%
Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 90 PSI (620.53 kPa) Operating Temperature -25°C ~ 85°C	Voltage - Supply	3 V ~ 16 V
Features Temperature Compensated Termination Style - Maximum Pressure 90 PSI (620.53 kPa) Operating Temperature -25°C ~ 85°C	Port Size	Male - 0.15" (3.8mm) Tube
Termination Style - Maximum Pressure 90 PSI (620.53 kPa) Operating Temperature -25°C ~ 85°C	Port Style	Barbed
Maximum Pressure 90 PSI (620.53 kPa) Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Features	Temperature Compensated
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Termination Style	-
	Maximum Pressure	90 PSI (620.53 kPa)
D 1 / C	Operating Temperature	-25°C ~ 85°C
Package / Case 4-SIP Module	Package / Case	4-SIP Module
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

CPC30AFH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CPC30AFH Payment Methods





















CPC30AFH Shipping Methods













If you have any question about CPC30AFH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com