

CPC5903G Information



For Reference Only

Part Number CPC5903G

Manufacturer IXYS Integrated Circuits Division

Category Isolators

Special Purpose

Description OPTOISO 3.75KV 1CH BIDIR 8DIP

Package 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CPC5903G Specifications

Manufacturer Part Number CPC5903G Manufacturer IXYS Integrated Circuits Division Category Isolators Package 8-DIP (0.300", 7.62mm) Series - Type I2C Repeater Number of Channels 2 Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) - Input Type I2C Current - Output / Channel - Propagation Delay tpLH / tpHL (Max) - Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Forward (If) (Max) - Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP Approvals UR, TUV		
Category Isolators Package 8-DIP (0.300", 7.62mm) Series - Type 12C Repeater Number of Channels 2 Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) - Input Type 12C Current - Output / Channel - Propagation Delay tpLH / tpHL (Max) - Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP Approvals UR, TUV	Manufacturer Part Number	CPC5903G
Package 8-DIP (0.300", 7.62mm) Series - Type I2C Repeater Number of Channels 2 Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) - Input Type I2C Current - Output / Channel - Propagation Delay tpLH / tpHL (Max) - Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP Approvals UR, TUV	Manufacturer	IXYS Integrated Circuits Division
Package 8-DIP (0.300", 7.62mm) Series - Type I2C Repeater Number of Channels 2 Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) - Input Type I2C Current - Output / Channel - Propagation Delay tpLH / tpHL (Max) - Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP Approvals UR, TUV	Category	Isolators
Series - Type I2C Repeater Number of Channels 2 Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) - Input Type I2C Current - Output / Channel - Propagation Delay tpLH / tpHL (Max) - Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP Approvals UR, TUV		Special Purpose
Type I2C Repeater Number of Channels 2 Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) - Input Type I2C Current - Output / Channel - Propagation Delay tpLH / tpHL (Max) - Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP Approvals UR, TUV	Package	8-DIP (0.300", 7.62mm)
Number of Channels Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) Input Type I2C Current - Output / Channel Propagation Delay tpLH / tpHL (Max) Rise / Fall Time (Typ) Voltage - Forward (Vf) (Typ) Current - DC Forward (If) (Max) Voltage - Supply Operating Temperature Mounting Type Through Hole Package / Case Approvals Approvals UR, TUV	Series	-
Voltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)-Input TypeI2CCurrent - Output / Channel-Propagation Delay tpLH / tpHL (Max)-Rise / Fall Time (Typ)-Voltage - Forward (Vf) (Typ)-Current - DC Forward (If) (Max)-Voltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-DIPApprovalsUR, TUV	Туре	I2C Repeater
Common Mode Transient Immunity (Min) Input Type I2C Current - Output / Channel Propagation Delay tpLH / tpHL (Max) Rise / Fall Time (Typ) Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) Voltage - Supply Operating Temperature Au°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Approvals LIC 12C 12C 12C 12C 12C 12C 12C 1	Number of Channels	2
Input Type Current - Output / Channel	Voltage - Isolation	3750Vrms
Current - Output / Channel Propagation Delay tpLH / tpHL (Max) Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package Approvals UR, TUV	Common Mode Transient Immunity (Min)	-
Propagation Delay tpLH / tpHL (Max) Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) Voltage - Supply Operating Temperature Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Approvals UR, TUV	Input Type	I2C
Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP Approvals UR, TUV	Current - Output / Channel	-
Voltage - Forward (Vf) (Typ) Current - DC Forward (If) (Max) Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package Approvals UR, TUV	Propagation Delay tpLH / tpHL (Max)	-
Current - DC Forward (If) (Max) Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package Approvals UR, TUV	Rise / Fall Time (Typ)	-
Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP UR, TUV	Voltage - Forward (Vf) (Typ)	-
Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP UR, TUV	Current - DC Forward (If) (Max)	-
Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP Approvals UR, TUV	Voltage - Supply	2.7 V ~ 5.5 V
Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP Approvals UR, TUV	Operating Temperature	-40°C ~ 85°C
Supplier Device Package 8-DIP Approvals UR, TUV	Mounting Type	Through Hole
Approvals UR, TUV	Package / Case	8-DIP (0.300", 7.62mm)
	Supplier Device Package	8-DIP
Report errors?	Approvals	UR, TUV
		Report errors?

CPC5903G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CPC5903G Payment Methods



















CPC5903G Shipping Methods













If you have any question about CPC5903G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com