

# CPCC0310R00KB32

### CPCC0310R00KB32 Information



Part Number	CPCC0310R00KB32	
Manufacturer	Vishay Dale	
Category	Resistors Through Hole Resistors	
Description	RES 10 OHM 3W 10% RADIAL	
Package	Radial	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## CPCC0310R00KB32 Specifications

Manufacturer Part NumberCPCC0310R00KB32ManufacturerVishay DaleCategoryResistorsThrough Hole ResistorsPackageRadialSeriesCPCCResistance10 OhmsTolerance±10%Power (Watts)3WCompositionViewoundFeaturesFlame Proof, SafetyOperating Temperaturee5°C ~ 275°CPackage / CaseRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)2Number of Terminations2Failure Rate-Failure RateFailure Rate- </th <th></th> <th></th>		
CategoryResistorsPackageRadialPackageRadialSeriesCPCCResistance10 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature65°C ~ 275°CPackage / CaseRadial LeadSize / Dimension0.984" (24.99mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	CPCC0310R00KB32
PackageThrough Hole ResistorsPackageRadialSeriesCPCCResistance10 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSuppler Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Manufacturer	Vishay Dale
PackageRadiaSeriesCPCCResistance10 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature65°C ~ 275°CPackage / CaseRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-	Category	Resistors
SeriesCPCCResistance10 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)2Number of Terminations2Failure Rate-		Through Hole Resistors
Resistance10 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)2Number of Terminations2Failure Rate-Failure Rate-State Safet Sa	Package	Radial
Tolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Series	CPCC
Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Resistance	10 Ohms
CompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Tolerance	±10%
FeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Power (Watts)	3W
Temperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Composition	Wirewound
Operating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Features	Flame Proof, Safety
Package / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±300ppm/°C
Supplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Operating Temperature	$-65^{\circ}C \sim 275^{\circ}C$
Size / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Package / Case	Radial
Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Supplier Device Package	Radial Lead
Number of Terminations2Failure Rate-	Size / Dimension	0.472" L x 0.315" W (12.00mm x 8.00mm)
Failure Rate -	Height - Seated (Max)	0.984" (24.99mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

#### CPCC0310R00KB32 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### CPCC0310R00KB32 Payment Methods



If you have any question about CPCC0310R00KB32, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com