

CPCC032R400KE66

CPCC032R400KE66 Information



Part Number	CPCC032R400KE66	
Manufacturer	Vishay Dale	
Category	Resistors Through Hole Resistors	
Description	RES 2.4 OHM 3W 10% RADIAL	
Package	Radial	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CPCC032R400KE66 Specifications

Manufacturer Part NumberCPCC032R400KE66ManufacturerVishay DaleCategoryResistorsThrough Hole ResistorsThrough Hole ResistorsPackageRadialSeriesCPCCResistance2.4 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±400ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-		
CategoryResistorsCategoryResistorsPackageRadialPackageRadialSeriesCPCCResistance2.4 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±400ppm/°COperating Temperature65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)2	Manufacturer Part Number	CPCC032R400KE66
Through Hole ResistorsPackageRadialSeriesCPCCResistance2.4 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±400ppm°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Manufacturer	Vishay Dale
PackageRadialPackageCPCCResistance2.4 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±400pm/°COperating Temperature65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)2	Category	Resistors
SeriesCPCCResistance2.4 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±400ppm/°COperating Temperature65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)2		Through Hole Resistors
Resistance2.4 OhmsTolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±400ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Package	Radial
Tolerance±10%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±400pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Series	CPCC
Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±400pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Resistance	2.4 Ohms
CompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±400ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Tolerance	±10%
FeaturesFlame Proof, SafetyTemperature Coefficient±400ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Power (Watts)	3W
Temperature Coefficient±400ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Composition	Wirewound
Operating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Features	Flame Proof, Safety
Package / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Temperature Coefficient	±400ppm/°C
Supplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Operating Temperature	-65°C ~ 275°C
Size / Dimension 0.472" L x 0.315" W (12.00mm x 8.00mm) Height - Seated (Max) 0.984" (24.99mm) Number of Terminations 2	Package / Case	Radial
Height - Seated (Max)0.984" (24.99mm)Number of Terminations2	Supplier Device Package	Radial Lead
Number of Terminations 2	Size / Dimension	0.472" L x 0.315" W (12.00mm x 8.00mm)
	Height - Seated (Max)	0.984" (24.99mm)
Failure Rate -	Number of Terminations	2
	Failure Rate	-
Report er		Report errors?

CPCC032R400KE66 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CPCC032R400KE66 Payment Methods



If you have any question about CPCC032R400KE66, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com