

CPCC1015R00KB31

CPCC1015R00KB31 Information



Part Number	CPCC1015R00KB31	
Manufacturer	Vishay Dale	
Category	Resistors Through Hole Resistors	
Description	RES 15 OHM 10W 10% RADIAL	
Package	Radial	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CPCC1015R00KB31 Specifications

Manufacturer Part Number CPCC1015R00KB31 Manufacturer Vishay Dale Category Resistors Category Radial Package Radial Series CPCC Resistance 150 Mms Tolerance ±10% Power (Watts) 10W Composition Wirewound Features Flame Proof, Safety Poperature Coefficient ±300pm/°C Operating Temperature e5°C ~ 275°C Package / Case Radial Lead Size / Dimension 0.633°L x 0.485°W (16.08mm x 12.32mm) Height - Seated (Max) 1.372°(34.85mm) Number of Terminations 2 Failure Rate -		
CategoryResistorsPackageRadialPackageRadialSeriesCPCCResistance15 OhmsTolerance±10%Power (Watts)IOWCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature65°C ~ 275°CPackage / CaseRadial LeadSuppler Device Package.633° L x 0.485° W (16.08mm x 12.32mm)Height - Seated (Max)2Number of Terminations2Failure Rate.	Manufacturer Part Number	CPCC1015R00KB31
PackageThrough Hole ResistorsPackageRadialSeriesCPCCResistance15 OhmsTolerance±10%Power (Watts)10WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.633" L x 0.485" W (16.08mm x 12.32mm)Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Manufacturer	Vishay Dale
PackageRadialSeriesCPCCResistance15 OhmsTolerance±10%Power (Watts)10WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating TemperatureRadial LeadSupplier Device PackageRadial LeadSize / Dimension1.372" (34.85mm)Height - Seated (Max)2Failure Rate-Failure Rate-Failure Rate-Failure Rate-Failure Rate-Failure Rate-Failure Rate-Failure Rate-	Category	Resistors
SeriesCPCCResistance15 OhmsTolerance±10%Power (Watts)10WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperaturee5°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.633° L x 0.485° W (16.08mm x 12.32mm)Height - Seated (Max)2Failure Rate-		Through Hole Resistors
Resistance15 OhmsTolerance±10%Power (Watts)10WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.633" L x 0.485" W (16.08mm x 12.32mm)Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Package	Radial
Tolerance±10%Power (Watts)10WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.633" L x 0.485" W (16.08mm x 12.32mm)Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Series	CPCC
Power (Watts)10WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.633" L x 0.485" W (16.08mm x 12.32mm)Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Resistance	15 Ohms
CompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.633" L x 0.485" W (16.08mm x 12.32mm)Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Tolerance	±10%
FeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.633" L x 0.485" W (16.08mm x 12.32mm)Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Power (Watts)	10W
Temperature Coefficient±300ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.633" L x 0.485" W (16.08mm x 12.32mm)Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Composition	Wirewound
Operating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.633" L x 0.485" W (16.08mm x 12.32mm)Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Features	Flame Proof, Safety
Package / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.633" L x 0.485" W (16.08mm x 12.32mm)Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±300ppm/°C
Supplier Device PackageRadial LeadSize / Dimension0.633" L x 0.485" W (16.08mm x 12.32mm)Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Operating Temperature	-65°C ~ 275°C
Number of Terminations 0.633" L x 0.485" W (16.08mm x 12.32mm) Failure Rate 0.633" L x 0.485" W (16.08mm x 12.32mm)	Package / Case	Radial
Height - Seated (Max)1.372" (34.85mm)Number of Terminations2Failure Rate-	Supplier Device Package	Radial Lead
Number of Terminations2Failure Rate-	Size / Dimension	0.633" L x 0.485" W (16.08mm x 12.32mm)
Failure Rate -	Height - Seated (Max)	1.372" (34.85mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

CPCC1015R00KB31 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CPCC1015R00KB31 Payment Methods





If you have any question about CPCC1015R00KB31, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com