



CPCL04DFC Information



For Reference Only

Part Number CPCL04DFC

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESSURE DIFF 4" H2O 4SIP

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CPCL04DFC Specifications

Manufacturer Part Number CPCL04DFC Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-SIP Module Series CPCL Pressure Type Differential Operating Pressure 0.15 PSI (1 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.16" (4.06mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PCB Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -			
Category Sensors, Transducers Pressure Sensors, Transducers Package 4-SIP Module Series CPCL Pressure Type Differential Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.16" (4.06mm) Tube, Dual Port Style Barbed Features Tempination Style Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case Supplications Sensors, Transducers Pressures 1 Fensors, Transducers 4-SIP Module Supplier Device Package - Sensors, Transducers Pressures 1 Fensors, Transducers 1 k-SIP Module - Supplier Device Package	Manufacturer Part Number	CPCL04DFC	
Package 4-SIP Module Series CPCL Pressure Type Differential Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.16" (4.06mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package4-SIP ModuleSeriesCPCLPressure TypeDifferentialOperating Pressure0.15 PSI (1 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 25 mV (12V)Accuracy±2%Voltage - Supply3 V ~ 16 VPort SizeMale - 0.16" (4.06mm) Tube, DualPort StyleBarbedFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure3 PSI (20.68 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Category	Sensors, Transducers	
SeriesCPCLPressure TypeDifferentialOperating Pressure0.15 PSI (1 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 25 mV (12V)Accuracy±2%Voltage - Supply3 V ~ 16 VPort SizeMale - 0.16" (4.06mm) Tube, DualPort StyleBarbedFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure3 PSI (20.68 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-		Pressure Sensors, Transducers	
Pressure Type Differential Operating Pressure 0.15 PSI (1 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.16" (4.06mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PCB Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Package	4-SIP Module	
Operating Pressure Output Type Wheatstone Bridge Output Output OmV ~ 25 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.16" (4.06mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PCB Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Series	CPCL	
Output TypeWheatstone BridgeOutput0 mV ~ 25 mV (12V)Accuracy±2%Voltage - Supply3 V ~ 16 VPort SizeMale - 0.16" (4.06mm) Tube, DualPort StyleBarbedFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure3 PSI (20.68 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Pressure Type	Differential	
Output 0 mV ~ 25 mV (12V) Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.16" (4.06mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PCB Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Operating Pressure	0.15 PSI (1 kPa)	
Accuracy ±2% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.16" (4.06mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PCB Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output Type	Wheatstone Bridge	
Voltage - Supply3 V ~ 16 VPort SizeMale - 0.16" (4.06mm) Tube, DualPort StyleBarbedFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure3 PSI (20.68 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Output	0 mV ~ 25 mV (12V)	
Port Size Male - 0.16" (4.06mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style PCB Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Accuracy	±2%	
Port Style Barbed Features Temperature Compensated Termination Style PCB Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Voltage - Supply	3 V ~ 16 V	
Features Temperature Compensated Termination Style PCB Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Port Size	Male - 0.16" (4.06mm) Tube, Dual	
Termination Style PCB Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Port Style	Barbed	
Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Features	Temperature Compensated	
Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Termination Style	PCB	
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	3 PSI (20.68 kPa)	
Supplier Device Package -	Operating Temperature	-25°C ~ 85°C	
	Package / Case	4-SIP Module	
Report errors?	Supplier Device Package	-	
		Report 6	errors?

CPCL04DFC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CPCL04DFC Payment Methods



















CPCL04DFC Shipping Methods













If you have any question about CPCL04DFC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com