

## CPCP0333R00FE32

## CPCP0333R00FE32 Information



Part Number	CPCP0333R00FE32	
Manufacturer	Vishay Dale	
Category	Resistors Through Hole Resistors	
Description	RES 33 OHM 3W 1% RADIAL	
Package	Radial	
	For the pricing/inventory/lead time, please contact	
	us Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

# For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## CPCP0333R00FE32 Specifications

Manufacturer Part Number CPCP0333R00FE32   Manufacturer Vishay Dale   Category Resistors   Through Hole Resistors Through Hole Resistors   Package Radial   Series CPCP   Resistance 33 Ohms   Tolerance ±1%   Power (Watts) 3W   Composition Wirewound   Features Flame Proof, Safety   Package / Case Radial Lead   Supplier Device Package Radial Lead   Size / Dimension 0.948" (24.99mm)   Number of Terminations 2   Number of Terminations 2		
CategoryResistorsPackageRadialPackageRadialSeriesCPCPResistance33 OhmsTolerance±1%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±20pm/°COperating TemperatureAcialSupplier Device PackageRadial LeadSize / Dimension0.947° L x 0.315° W (12.00mm x 8.00mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Manufacturer Part Number	CPCP0333R00FE32
Through Hole ResistorsPackageRadialSeriesCPCPResistance33 OhmsTolerance±1%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyOperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.944" (24.99mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Manufacturer	Vishay Dale
PackageRadialSeriesCPCPResistance33 OhmsTolerance±1%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyOperating Temperature-65°C ~275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)2Number of Terminations2Failure Rate-Failure Rate-<	Category	Resistors
SeriesCPCPResistance33 OhmsTolerance±1%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±20pm/°COperating Temperature-65° C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-		Through Hole Resistors
Resistance33 OhmsTolerance±1%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±20pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Package	Radial
Tolerance±1%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±20pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Series	CPCP
Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±20pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Resistance	33 Ohms
CompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient $\pm 20 ppm^{\circ}C$ Operating Temperature $-65^{\circ}C \sim 275^{\circ}C$ Package / CaseRadial LeadSupplier Device Package $0.472^{\circ}L x \ 0.315^{\circ}W \ 12.00 mm x \ 8.00 mm)$ Height - Seated (Max) $0.984^{\circ}(24.99 mm)$ Number of Terminations $2$ Failure Rate $-$	Tolerance	$\pm 1\%$
FeaturesFlame Proof, SafetyTemperature Coefficient±20ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Power (Watts)	3W
Temperature Coefficient±20ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Composition	Wirewound
Operating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Features	Flame Proof, Safety
Package / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±20ppm/°C
Supplier Device PackageRadial LeadSize / Dimension0.472" L x 0.315" W (12.00mm x 8.00mm)Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Operating Temperature	-65°C ~ 275°C
Number of Terminations0.472" L x 0.315" W (12.00mm x 8.00mm)Number of Terminations2Failure Rate-	Package / Case	Radial
Height - Seated (Max)0.984" (24.99mm)Number of Terminations2Failure Rate-	Supplier Device Package	Radial Lead
Number of Terminations2Failure Rate-	Size / Dimension	0.472" L x 0.315" W (12.00mm x 8.00mm)
Failure Rate -	Height - Seated (Max)	0.984" (24.99mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
Report citors.		Report errors?

### CPCP0333R00FE32 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### CPCP0333R00FE32 Payment Methods





If you have any question about CPCP0333R00FE32, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com