

CPM373030C.A

Quote

CPM373030C.A Information

Heisener.com	Part Number Manufacturer Category Description Package	CPM373030C.A Crouzet Sensors, Transducers Proximity Sensors SENS PROX CAP M30 PNP NO-NC 2M Cylinder, Threaded - M30 For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CPM373030C.A Specifications

Manufacturer Part NumberCPM373030C.AManufacturerCrouzetCategorySensors, TransducersPackageProximity SensorsPackageCylinder, Threaded - M30Series-Sensor TypeCapacitiveSensing Distance0.118" ~ 1.181" (3mm ~ 30mm)Output TypePNP-NC, 3-WireResponse Frequency-ShieldingUnshieldedMaterial - BodyPlasticVoltage - Supply10 V ~ 30 VOperating Temperature-25°C ~ 70°CIngress ProtectionIEDIndicatorLEDVackage / CaseCylinder, Threaded - M30		
CategorySensors, TransducersPackageProximity SensorsPackageCylinder, Threaded - M30Series-Sensor TypeCapacitiveSensing Distance0.118" ~ 1.181" (3mm ~ 30mm)Output TypePNP-NC, 3-WireResponse Frequency-ShieldingUnshieldedMaterial - BodyPlasticVoltage - Supply10 V ~ 30 VTermination Style-Stor 20°C ~ 70°CIngress ProtectionIEDIndicatorLEDPackage / CaseStylinder, Threaded - M30	Manufacturer Part Number	CPM373030C.A
PackageProximity SensorsPackageCylinder, Threaded - M30Series-Sensor TypeCapacitiveSensing Distance0.118" ~ 1.181" (3mm ~ 30mm)Output TypePNP-NC, 3-WireResponse Frequency-ShieldingUnshieldedMaterial - BodyPlasticVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionHEDPackage / CaseCylinder, Threaded - M30	Manufacturer	Crouzet
PackageCylinder, Threaded - M30Series-Sensor TypeCapacitiveSensing Distance0.118" ~ 1.181" (3mm ~ 30mm)Output TypePNP-NC, 3-WireResponse Frequency-ShieldingUnshieldedMaterial - BodyPlasticVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionLEDPackage / CaseCylinder, Threaded - M30	Category	Sensors, Transducers
Series-Sensor TypeCapacitiveSensing Distance0.118" ~ 1.181" (3mm ~ 30mm)Output TypePNP-NC, 3-WireResponse Frequency-ShieldingUnshieldedMaterial - BodyPlasticVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M30		Proximity Sensors
Sensor TypeCapacitiveSensing Distance0.118" ~ 1.181" (3mm ~ 30mm)Output TypePNP-NC, 3-WireResponse Frequency-ShieldingUnshieldedMaterial - BodyPlasticVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating TemperatureP65IndicatorLEDPackage / CaseCylinder, Threaded - M30	Package	Cylinder, Threaded - M30
Sensing Distance0.118" ~ 1.181" (3mm ~ 30mm)Output TypePNP-NC, 3-WireResponse Frequency-ShieldingUnshieldedMaterial - BodyPlasticVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M30	Series	-
Output TypePNP-NC, 3-WireResponse Frequency-ShieldingUnshieldedMaterial - BodyPlasticVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M30	Sensor Type	Capacitive
Response Frequency-ShieldingUnshieldedMaterial - BodyPlasticVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M30	Sensing Distance	0.118" ~ 1.181" (3mm ~ 30mm)
ShieldingUnshieldedMaterial - BodyPlasticVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M30	Output Type	PNP-NC, 3-Wire
Material - BodyPlasticVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M30	Response Frequency	-
Voltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M30	Shielding	Unshielded
Termination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M30	Material - Body	Plastic
Operating Temperature-25°C ~ 70°CIngress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M30	Voltage - Supply	10 V ~ 30 V
Ingress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M30	Termination Style	Cable Leads
IndicatorLEDPackage / CaseCylinder, Threaded - M30	Operating Temperature	$-25^{\circ}C \sim 70^{\circ}C$
Package / Case Cylinder, Threaded - M30	Ingress Protection	IP65
	Indicator	LED
	Package / Case	Cylinder, Threaded - M30
Report errors'		Report errors?

CPM373030C.A Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CPM373030C.A Payment Methods



CPM373030C.A Shipping Methods



If you have any question about CPM373030C.A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com