



CPPLC7-HT5PT Information



For Reference Only

Part Number CPPLC7-HT5PT

Manufacturer Cardinal Components Inc.

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG CMOS 5V TRI ST 50PPM

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CPPLC7-HT5PT Specifications

Manufacturer Part Number CPPLC7-HTSPT Manufacturer Cardinal Components Inc. Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)		
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)	Manufacturer Part Number	CPPLC7-HT5PT
Package 4-SMD, No Lead Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)	Manufacturer	Cardinal Components Inc.
Package 4-SMD, No Lead Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)	Category	Crystals, Oscillators, Resonators
Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)		Programmable Oscillators
Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.075" (1.90mm) Kasings 1-MC (1.90mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height MHz ~ 133MHz IMHz ~ 133MHz IME ~ 133MHz IMHz ~ 133MHz IMIT ~ 133MHz	Series	FIPO? CPPL
Available Frequency Range Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability Frequency Stability (Total) Operating Temperature Operating Temperature Spread Spectrum Bandwidth - Current - Supply (Max) Asings - Mounting Type Surface Mount Package / Case Size / Dimension Output Enable/Disable Enabl	Туре	XO (Standard)
Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.00000000000000000000000000000000000	Programmable Type	Programmed as Request
OutputCMOSVoltage - Supply5VFrequency Stability±50ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.075" (1.90mm)	Available Frequency Range	1MHz ~ 133MHz
Voltage - Supply5VFrequency Stability±50ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.075" (1.90mm)	Function	Enable/Disable
Frequency Stability (Total)	Output	CMOS
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height	Voltage - Supply	5V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)	Frequency Stability	±50ppm
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)	Frequency Stability (Total)	-
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)	Current - Supply (Max)	45mA
Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)	Ratings	-
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.075" (1.90mm)	Mounting Type	Surface Mount
Height 0.075" (1.90mm)	Package / Case	4-SMD, No Lead
-	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height	0.075" (1.90mm)
		Report errors?

CPPLC7-HT5PT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CPPLC7-HT5PT Payment Methods



















CPPLC7-HT5PT Shipping Methods













If you have any question about CPPLC7-HT5PT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com