



### **CPPLT1-LT76T Information**



For Reference Only

Part Number CPPLT1-LT76T

Manufacturer Cardinal Components Inc.

Category Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description** OSC PROG TTL 3.3V TRI ST 100PPM **Package** 14-DIP, 4 Leads (Full Size, Metal Can)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CPPLT1-LT76T Specifications**

Manufacturer Part Number         CPPLT1-LT76T           Manufacturer         Cardinal Components Inc.           Category         Crystals, Oscillators, Resonators           Package         14-DIP, 4 Leads (Full Size, Metal Can)           Series         FIPO? CPPL           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 100MHz           Function         Enable/Disable           Output         TTL           Voltage - Supply         3.3V           Frequency Stability         ±100ppm           Frequency Stability (Total)         -           Operating Temperature         +40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         25mA           Ratings         -           Mounting Type         Through Hole           Package / Case         14-DIP, 4 Leads (Full Size, Metal Can)           Size / Dimension         0.819" L x 0.520" W (20.80mm x 13.20mm)           Height         0.200" (5.08mm)		
Category         Crystals, Oscillators, Resonators           Package         14-DIP, 4 Leads (Full Size, Metal Can)           Series         FIPO? CPPL           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 100MHz           Function         Enable/Disable           Output         TTL           Voltage - Supply         3.3V           Frequency Stability (Total)         -           Operating Temperature         40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         25mA           Ratings         -           Mounting Type         Through Hole           Package / Case         14-DIP, 4 Leads (Full Size, Metal Can)           Size / Dimension         0.819" L x 0.520" W (20.80mm x 13.20mm)           Height         0.200" (5.08mm)	Manufacturer Part Number	CPPLT1-LT76T
Package 14-DIP, 4 Leads (Full Size, Metal Can) Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 100MHz Function Enable/Disable Output TTL Voltage - Supply 3.3V Frequency Stability Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 14-DIP, 4 Leads (Full Size, Metal Can) Size / Dimension 0.819" L x 0.520" W (20.80mm x 13.20mm) Height 0.200" (5.08mm)	Manufacturer	Cardinal Components Inc.
Package         14-DIP, 4 Leads (Full Size, Metal Can)           Series         FIPO? CPPL           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 100MHz           Function         Enable/Disable           Output         TTL           Voltage - Supply         3.3V           Frequency Stability         ±100ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         25mA           Ratings         -           Mounting Type         Through Hole           Package / Case         14-DIP, 4 Leads (Full Size, Metal Can)           Size / Dimension         0.819" L x 0.520" W (20.80mm x 13.20mm)           Height         0.200" (5.08mm)	Category	Crystals, Oscillators, Resonators
Series         FIPO? CPPL           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 100MHz           Function         Enable/Disable           Output         TTL           Voltage - Supply         3.3V           Frequency Stability         ±100ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         25mA           Ratings         -           Mounting Type         Through Hole           Package / Case         14-DIP, 4 Leads (Full Size, Metal Can)           Size / Dimension         0.819" L x 0.520" W (20.80mm x 13.20mm)           Height         0.200" (5.08mm)		Programmable Oscillators
TypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 100MHzFunctionEnable/DisableOutputTTLVoltage - Supply3.3VFrequency Stability±100ppmFrequency Stability (Total)-Operating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)25mARatings-Mounting TypeThrough HolePackage / Case14-DIP, 4 Leads (Full Size, Metal Can)Size / Dimension0.819" L x 0.520" W (20.80mm x 13.20mm)Height0.200" (5.08mm)	Package	14-DIP, 4 Leads (Full Size, Metal Can)
Programmable Type Programmed as Request  Available Frequency Range 1MHz ~ 100MHz  Function Enable/Disable  Output TTL  Voltage - Supply 3.3V  Frequency Stability ±100ppm  Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 25mA  Ratings - Mounting Type Through Hole  Package / Case 14-DIP, 4 Leads (Full Size, Metal Can)  Size / Dimension 0.819" L x 0.520" W (20.80mm x 13.20mm)  Height 0.200" (5.08mm)	Series	FIPO? CPPL
Available Frequency Range  IMHz ~ 100MHz  Function  Enable/Disable  Output  TTL  Voltage - Supply  3.3V  Frequency Stability  # 100ppm  Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  -  Current - Supply (Max)  Ratings  -  Mounting Type  Through Hole  Package / Case  14-DIP, 4 Leads (Full Size, Metal Can)  Size / Dimension  0.819" L x 0.520" W (20.80mm x 13.20mm)  Height	Туре	XO (Standard)
Function Enable/Disable Output TTL Voltage - Supply 3.3V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 14-DIP, 4 Leads (Full Size, Metal Can) Size / Dimension 0.200" (5.08mm)	Programmable Type	Programmed as Request
Output TTL  Voltage - Supply 3.3V  Frequency Stability ±100ppm  Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 25mA  Ratings - Mounting Type Through Hole  Package / Case 14-DIP, 4 Leads (Full Size, Metal Can)  Size / Dimension 0.819" L x 0.520" W (20.80mm x 13.20mm)  Height 0.200" (5.08mm)	Available Frequency Range	1MHz ~ 100MHz
Voltage - Supply  3.3V  Frequency Stability  Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  25mA  Ratings  - Mounting Type  Through Hole  Package / Case  14-DIP, 4 Leads (Full Size, Metal Can)  Size / Dimension  0.819" L x 0.520" W (20.80mm x 13.20mm)  Height  0.200" (5.08mm)	Function	Enable/Disable
Frequency Stability (Total)	Output	TTL
Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  25mA  Ratings  - Mounting Type  Through Hole  Package / Case  14-DIP, 4 Leads (Full Size, Metal Can)  Size / Dimension  0.819" L x 0.520" W (20.80mm x 13.20mm)  Height  0.200" (5.08mm)	Voltage - Supply	3.3V
Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 25mA  Ratings - Mounting Type Through Hole  Package / Case 14-DIP, 4 Leads (Full Size, Metal Can) Size / Dimension 0.819" L x 0.520" W (20.80mm x 13.20mm)  Height 0.200" (5.08mm)	Frequency Stability	±100ppm
Spread Spectrum Bandwidth  Current - Supply (Max)  Ratings  - Mounting Type  Through Hole  Package / Case  14-DIP, 4 Leads (Full Size, Metal Can)  Size / Dimension  0.819" L x 0.520" W (20.80mm x 13.20mm)  Height  0.200" (5.08mm)	Frequency Stability (Total)	-
Current - Supply (Max)  Ratings  - Mounting Type  Through Hole  Package / Case  14-DIP, 4 Leads (Full Size, Metal Can)  Size / Dimension  0.819" L x 0.520" W (20.80mm x 13.20mm)  Height  0.200" (5.08mm)	Operating Temperature	-40°C ~ 85°C
Ratings -  Mounting Type Through Hole  Package / Case 14-DIP, 4 Leads (Full Size, Metal Can)  Size / Dimension 0.819" L x 0.520" W (20.80mm x 13.20mm)  Height 0.200" (5.08mm)	Spread Spectrum Bandwidth	-
Mounting Type Through Hole Package / Case 14-DIP, 4 Leads (Full Size, Metal Can) Size / Dimension 0.819" L x 0.520" W (20.80mm x 13.20mm) Height 0.200" (5.08mm)	Current - Supply (Max)	25mA
Package / Case       14-DIP, 4 Leads (Full Size, Metal Can)         Size / Dimension       0.819" L x 0.520" W (20.80mm x 13.20mm)         Height       0.200" (5.08mm)	Ratings	-
Size / Dimension       0.819" L x 0.520" W (20.80mm x 13.20mm)         Height       0.200" (5.08mm)	Mounting Type	Through Hole
Height 0.200" (5.08mm)	Package / Case	14-DIP, 4 Leads (Full Size, Metal Can)
	Size / Dimension	0.819" L x 0.520" W (20.80mm x 13.20mm)
Report errors?	Height	0.200" (5.08mm)
		Report errors?

#### **CPPLT1-LT76T Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CPPLT1-LT76T Payment Methods**





















### **CPPLT1-LT76T Shipping Methods**













If you have any question about CPPLT1-LT76T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com