



### **CPPT4-LT76P Information**



For Reference Only

Part Number CPPT4-LT76P

Manufacturer Cardinal Components Inc.

**Category** Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description** OSC PROG TTL 3.3V STBY 100PPM TH

Package 8-DIP, 4 Leads (Half Size, Metal Can)
For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CPPT4-LT76P Specifications**

Manufacturer Part Number         CPPT4-LT76P           Manufacturer         Cardinal Components Inc.           Category         Crystals, Oscillators, Resonators           Package         8-DIP, 4 Leads (Half Size, Metal Can)           Series         FIPO? CPP           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 100MHz           Function         Standby           Output         TTL           Voltage - Supply         3.3V           Frequency Stability         ±100ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         25mA           Ratings         -           Mounting Type         Through Hole           Package / Case         8-DIP, 4 Leads (Half Size, Metal Can)           Size / Dimension         0.520" L x 0.520" W (13.20mm x 13.20mm)           Height         0.220" (5.60mm)		
Category         Crystals, Oscillators, Resonators           Package         8-DIP, 4 Leads (Half Size, Metal Can)           Series         FIPO? CPP           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 100MHz           Function         Standby           Output         TTL           Voltage - Supply         3.3V           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         25mA           Ratings         -           Mounting Type         Through Hole           Package / Case         8-DIP, 4 Leads (Half Size, Metal Can)           Size / Dimension         0.520" Lx 0.520" W (13.20mm x 13.20mm)           Height         0.220" (5.60mm)	Manufacturer Part Number	CPPT4-LT76P
Package 8-DIP, 4 Leads (Half Size, Metal Can) Series FIPO? CPP Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 100MHz Function Standby Output TTL Voltage - Supply 3.3V Frequency Stability Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Manufacturer	Cardinal Components Inc.
Package         8-DIP, 4 Leads (Half Size, Metal Can)           Series         FIPO? CPP           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 100MHz           Function         Standby           Output         TTL           Voltage - Supply         3.3V           Frequency Stability         ±100ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         25mA           Ratings         -           Mounting Type         Through Hole           Package / Case         8-DIP, 4 Leads (Half Size, Metal Can)           Size / Dimension         0.520" L x 0.520" W (13.20mm x 13.20mm)           Height         0.220" (5.60mm)	Category	Crystals, Oscillators, Resonators
Series         FIPO? CPP           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 100MHz           Function         Standby           Output         TTL           Voltage - Supply         3.3V           Frequency Stability         ±100ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         25mA           Ratings         -           Mounting Type         Through Hole           Package / Case         8-DIP, 4 Leads (Half Size, Metal Can)           Size / Dimension         0.520" L x 0.520" W (13.20mm x 13.20mm)           Height         0.220" (5.60mm)		Programmable Oscillators
TypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 100MHzFunctionStandbyOutputTTLVoltage - Supply3.3VFrequency Stability±100ppmFrequency Stability (Total)-Operating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)25mARatings-Mounting TypeThrough HolePackage / Case8-DIP, 4 Leads (Half Size, Metal Can)Size / Dimension0.520" L x 0.520" W (13.20mm x 13.20mm)Height0.220" (5.60mm)	Package	8-DIP, 4 Leads (Half Size, Metal Can)
Programmable Type Programmed as Request  Available Frequency Range 1MHz ~ 100MHz  Function Standby  Output TTL  Voltage - Supply 3.3V  Frequency Stability ±100ppm  Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 25mA  Ratings - Mounting Type Through Hole  Package / Case 8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm)  Height 0.220" (5.60mm)	Series	FIPO? CPP
Available Frequency Range  IMHz ~ 100MHz  Function  Standby  Output  TTL  Voltage - Supply  3.3V  Frequency Stability  ±100ppm  Frequency Stability (Total)  - Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Through Hole  Package / Case  8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension  0.520" L x 0.520" W (13.20mm x 13.20mm)  Height	Туре	XO (Standard)
Function Standby Output TTL Voltage - Supply 3.3V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.220" (5.60mm)	Programmable Type	Programmed as Request
Output TTL Voltage - Supply 3.3V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Available Frequency Range	1MHz ~ 100MHz
Voltage - Supply  3.3V  Frequency Stability  Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  25mA  Ratings  - Mounting Type  Through Hole  Package / Case  8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension  0.520" L x 0.520" W (13.20mm x 13.20mm)  Height  0.220" (5.60mm)	Function	Standby
Frequency Stability (Total)	Output	TTL
Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Through Hole  Package / Case  8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension  0.520" L x 0.520" W (13.20mm x 13.20mm)  Height  - 0.220" (5.60mm)	Voltage - Supply	3.3V
Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 25mA  Ratings - Mounting Type Through Hole  Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm)  Height 0.220" (5.60mm)	Frequency Stability	±100ppm
Spread Spectrum Bandwidth  Current - Supply (Max)  Ratings  - Mounting Type  Through Hole  Package / Case  8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension  0.520" L x 0.520" W (13.20mm x 13.20mm)  Height  0.220" (5.60mm)	Frequency Stability (Total)	-
Current - Supply (Max)  Ratings  - Mounting Type  Through Hole  Package / Case  8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension  0.520" L x 0.520" W (13.20mm x 13.20mm)  Height  0.220" (5.60mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Spread Spectrum Bandwidth	-
Mounting Type Through Hole  Package / Case 8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm)  Height 0.220" (5.60mm)	Current - Supply (Max)	25mA
Package / Case         8-DIP, 4 Leads (Half Size, Metal Can)           Size / Dimension         0.520" L x 0.520" W (13.20mm x 13.20mm)           Height         0.220" (5.60mm)	Ratings	-
Size / Dimension       0.520" L x 0.520" W (13.20mm x 13.20mm)         Height       0.220" (5.60mm)	Mounting Type	Through Hole
Height 0.220" (5.60mm)	Package / Case	8-DIP, 4 Leads (Half Size, Metal Can)
	Size / Dimension	0.520" L x 0.520" W (13.20mm x 13.20mm)
Report errors?	Height	0.220" (5.60mm)
		Report errors?

#### **CPPT4-LT76P Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **CPPT4-LT76P Payment Methods**



















### **CPPT4-LT76P Shipping Methods**













If you have any question about CPPT4-LT76P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com