



### **CPPT8-HT5RT Information**



For Reference Only

Part Number CPPT8-HT5RT

Manufacturer Cardinal Components Inc.

Category Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description** OSC PROG TTL 5V TRI ST 25PPM SMD

**Package** 4-SOJ, 7.62mm pitch

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CPPT8-HT5RT Specifications**

Manufacturer Part NumberCPPT8-HT5RTManufacturerCardinal Components Inc.CategoryCrystals, Oscillators, ResonatorsPackage4-SOJ, 7.62mm pitchSeriesFIPO? CPPTypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency RangeIMHz ~ 133MHzFunctionEnable/DisableOutputTTLVoltage - Supply5VFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface MountPackage / Case4-SOJ, 7.62mm pitch		
Category Crystals, Oscillators, Resonators Programmable Oscillators Package 4-SOJ, 7.62mm pitch Series FIPO? CPP Type XO (Standard) Programmable Type Programmable Type Programmed as Request Available Frequency Range IMHz ~ 133MHz Function Enable/Disable Output TTL Voltage - Supply SV Frequency Stability ±25ppm Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings Aussillators, Resonators Programmable Oscillators Programmable	Manufacturer Part Number	CPPT8-HT5RT
Package 4-SOJ, 7.62mm pitch Series FIPO? CPP Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 133MHz Function Enable/Disable Output TTL Voltage - Supply 5V Frequency Stability + ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount	Manufacturer	Cardinal Components Inc.
Package4-SOJ, 7.62mm pitchSeriesFIPO? CPPTypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 133MHzFunctionEnable/DisableOutputTTLVoltage - Supply5VFrequency Stability±25ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface Mount	Category	Crystals, Oscillators, Resonators
SeriesFIPO? CPPTypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 133MHzFunctionEnable/DisableOutputTTLVoltage - Supply5VFrequency Stability±25ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface Mount		Programmable Oscillators
Type XO (Standard) Programmable Type Programmed as Request  Available Frequency Range 1MHz ~ 133MHz  Function Enable/Disable Output TTL  Voltage - Supply 5V  Frequency Stability + ±25ppm  Frequency Stability (Total) - 20°C ~ 70°C  Spread Spectrum Bandwidth - Current - Supply (Max) 45mA  Ratings - Surface Mount	Package	4-SOJ, 7.62mm pitch
Programmable Type Programmed as Request  Available Frequency Range 1MHz ~ 133MHz  Function Enable/Disable  Output TTL  Voltage - Supply 5V  Frequency Stability ±25ppm  Frequency Stability (Total) -  Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 45mA  Ratings -  Mounting Type Surface Mount	Series	FIPO? CPP
Available Frequency Range  Function  Enable/Disable  Output  TTL  Voltage - Supply  Frequency Stability  Frequency Stability (Total)  Operating Temperature  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  Mounting Type  IMHz ~ 133MHz  Enable/Disable  TTL  5V  TOL  TOL  TOL  TOL  TOL  TOL  TOL  TO	Туре	XO (Standard)
Function Enable/Disable  Output TTL  Voltage - Supply 5V  Frequency Stability ±25ppm  Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth - Current - Supply (Max) 45mA  Ratings - Mounting Type Surface Mount	Programmable Type	Programmed as Request
Output TTL  Voltage - Supply 5V  Frequency Stability ±25ppm  Frequency Stability (Total) -  Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 45mA  Ratings -  Mounting Type Surface Mount	Available Frequency Range	1MHz ~ 133MHz
Voltage - Supply5VFrequency Stability±25ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface Mount	Function	Enable/Disable
Frequency Stability (Total)  Operating Temperature  -20°C ~ 70°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  ±25ppm  -20°C ~ 70°C  -20	Output	TTL
Frequency Stability (Total)  Operating Temperature  -20°C ~ 70°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount	Voltage - Supply	5V
Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 45mA  Ratings -  Mounting Type Surface Mount	Frequency Stability	±25ppm
Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount	Frequency Stability (Total)	-
Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount	Current - Supply (Max)	45mA
	Ratings	-
Package / Case 4-SOJ, 7.62mm pitch	Mounting Type	Surface Mount
	Package / Case	4-SOJ, 7.62mm pitch
Size / Dimension 0.551" L x 0.341" W (14.00mm x 8.65mm)	Size / Dimension	0.551" L x 0.341" W (14.00mm x 8.65mm)
Height 0.185" (4.70mm)	Height	0.185" (4.70mm)
Report error		Report errors?

### **CPPT8-HT5RT Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CPPT8-HT5RT Payment Methods**



















## **CPPT8-HT5RT Shipping Methods**













If you have any question about CPPT8-HT5RT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com