

CPR039R100JE31

CPR039R100JE31 Information



umber	CPR039R100JE31	
facturer	Vishay Dale	
ory	Resistors Through Hole Resistors	
ption	RES 9.1 OHM 3W 5% RADIAL	
ge	Radial	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CPR039R100JE31 Specifications

Manufacturer Part Number CPR039R100JE31 Manufacturer Vishay Dale Category Resistors Category Through Hole Resistors Package Radial Series CPR Resistance 9.1 Ohms Tolerance ±5% Power (Watts) 3W Composition Virewound Features Flame Proof, Safety Poperature Coefficient ±300ppn/°C Operating Temperature -65°C ~ 275°C Package / Case Radial Lead Size / Dimension 0.906" L x 0.375" W (23.00mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Number of Terminations 2		
CategoryResistorsThrough Hole ResistorsPackageRadialSeriesCPRResistance9.1 OhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperaturec5°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.906° L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)0.375" (9.633mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	CPR039R100JE31
Through Hole ResistorsPackageRadialSeriesCPRResistance9.1 OhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTomperature Coefficient±300pm/°COperating Temperaturee65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Manufacturer	Vishay Dale
PackageRadiaSeriesCPRResistance9.1 OhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperaturee6°C ~ 275°CPackage / CaseRadial LeadSize / Dimension0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-	Category	Resistors
SeriesCPRResistance9.1 OhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.906° L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)2Number of Terminations2Failure Rate-		Through Hole Resistors
Resistance9.1 OhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300ppm/°COperating Temperature65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Number of Terminations2Failure Rate-	Package	Radial
Tolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Number of Terminations2Failure Rate-	Series	CPR
Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Number of Terminations2Failure Rate-	Resistance	9.1 Ohms
CompositionWirewoundFeaturesFlame Proof, SafetyTemperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Tolerance	$\pm 5\%$
FeaturesFlame Proof, SafetyTemperature Coefficient±300ppm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Number of Terminations2Failure Rate-	Power (Watts)	3W
Temperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Number of Terminations2Failure Rate-	Composition	Wirewound
Operating Temperature-65°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Number of Terminations2Failure Rate-	Features	Flame Proof, Safety
Package / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±300ppm/°C
Supplier Device PackageRadial LeadSize / Dimension0.906" L x 0.375" W (23.00mm x 9.53mm)Height - Seated (Max)0.375" (9.53mm)Number of Terminations2Failure Rate-	Operating Temperature	-65°C ~ 275°C
Size / Dimension 0.906" L x 0.375" W (23.00mm x 9.53mm) Height - Seated (Max) 0.375" (9.53mm) Number of Terminations 2 Failure Rate -	Package / Case	Radial
Height - Seated (Max)0.375" (9.53mm)Number of Terminations2Failure Rate-	Supplier Device Package	Radial Lead
Number of Terminations2Failure Rate-	Size / Dimension	0.906" L x 0.375" W (23.00mm x 9.53mm)
Failure Rate -	Height - Seated (Max)	0.375" (9.53mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
*		Report errors?

CPR039R100JE31 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CPR039R100JE31 Payment Methods





If you have any question about CPR039R100JE31, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com