

CS3102A-48-53S Information

Heisener.com

Part Number CS3102A-48-53S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors**

Description

CONN RCPT 37POS BOX MNT SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CS3102A-48-53S Specifications

Manufacturer Part Number CS3102A-48-53S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series CS, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 37 Shell Size - Insert 48-53 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series CS, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 37 Shell Size - Insert 48-53 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Manufacturer Part Number	CS3102A-48-53S
Circular Connectors Package - Series CS, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 37 Shell Size - Insert 48-53 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - CS, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 37 Shell Size - Insert 48-53 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Woltage - Rated 900VAC, 1250VDC Current Rating	Category	Connectors, Interconnects
Series CS, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 37 Shell Size - Insert 48-53 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 37 Shell Size - Insert 48-53 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Package	-
Number of Positions Shell Size - Insert 48-53 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 900VAC, 1250VDC Current Rating	Series	CS, MIL-5015 Derivative
Shell Size - Insert 48-53 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Number of Positions	37
Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size - Insert	48-53
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating - Aluminum Alloy, Olive Drab Cadmium Plated - Silver Voltage - Rated	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC - Current Rating -	Ingress Protection	-
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

CS3102A-48-53S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CS3102A-48-53S Payment Methods



















CS3102A-48-53S Shipping Methods













If you have any question about CS3102A-48-53S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com