

CSS1206DT10L0

CSS1206DT10L0 Information

Heisener.com	 CSS1206DT10L0 Stackpole Electronics Inc. Resistors Chip Resistor - Surface Mount RES SMD 0.01 OHM 0.5% 1W 1206 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CSS1206DT10L0 Specifications

Manufacturer Part NumberCSS1206DT10L0ManufacturerStackpole Electronics Inc.CategoryResistorsChip Resistor - Surface MountPackage1206 (3216 Metric)SeriesCSSResistance10 mOhmsTolerance±0.5%Power (Watts)IWCompositionMetal FoilFeaturesAutomotive AEC-Q200, Current SensePoperature Coefficient±25pm/°COperating Temperature50°C ~ 225°CPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.035" (0.90mm)Number of Terminations2Package2Package2Package / Case0.035" (0.90mm)Stack (Max)0.035" (0.90mm)Number of Terminations2Package / Case2Package / Case2Size / Dimension0.25" (0.90mm)Stack (Max)0.035" (0.90mm)Package / Case2Size / Dimension2Stack (Max)0.935" (0.90mm)Stack (Max)2Stack (Max)2Stack (Max)2Stack (Max)2Stack (Max)3Stack (Max)3Stack (Max)3Stack (Max)3Stack (Max)3Stack (Max)3Stack (Max)3Stack (Max)3Stack (Max)3Stack (Max)3			
CategoryResistorsChip Resistor - Surface MountPackage1206 (3216 Metric)SeriesCSSResistance10 mOhmsTolerance±0.5%Power (Watts)IWCompositionMetal FoilFeaturesAutomotive AEC-Q200, Current SenseTemperature Coefficient±25pm/°COperating Temperature1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.035" (0.90mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	CSS1206DT10L0	
Chip Resistor - Surface MountPackage1206 (3216 Metric)SeriesCSSResistance10 mOhmsTolerance±0.5%Power (Watts)IWCompositionMetal FoilFeaturesAutomotive AEC-Q200, Current SenseToperature Coefficient±25pm/°COperating Temperature-55°C ~ 225°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Number of Terminations2Failure Rate-	Manufacturer	Stackpole Electronics Inc.	
Package1206 (3216 Metric)SeriesCSSResistance10 mOhmsTolerance±0.5%Power (Wats)IWCompositionMetal FoilFeaturesAutomotive AEC-Q200, Current SensePoperating Temperature±25ppm/°COperating Temperature1206 (3216 Metric)Supplier Device Package1026 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Category	Resistors	
Series CSS Resistance 10 mOhms Tolerance ±0.5% Power (Watts) 1W Composition Metal Foil Features Automotive AEC-Q200, Current Sense Temperature Coefficient ±25pm/°C Operating Temperature -55°C ~ 225°C Package / Case 1206 (3216 Metric) Supplier Device Package 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.035" (0.90mm) Number of Terminations 2 Failure Rate -		Chip Resistor - Surface Mount	
Resistance10 mOhmsTolerance±0.5%Power (Watts)IWCompositionMetal FoilFeaturesAutomotive AEC-Q200, Current SenseTemperature Coefficient±25pm/°COperating Temperature55°C ~ 225°CPackage / Case1206 (3216 Metric)Supplier Device Package0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.035" (0.90mm)Number of Terminations2Failure Rate-	Package	1206 (3216 Metric)	
Tolerance±0.5%Power (Watts)IWCompositionMetal FoilFeaturesAutomotive AEC-Q200, Current SenseTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 225°CPackage / Case1206 (3216 Metric)Supplier Device Package0.126" L x 0.063" W (3.20mm x 1.60mm)Keight - Seated (Max)0.035" (0.90mm)Number of Terminations2Failure Rate-	Series	CSS	
Power (Watts)IWCompositionMetal FoilFeaturesAutomotive AEC-Q200, Current SenseTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 225°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.035" (0.90mm)Number of Terminations2Failure Rate-	Resistance	10 mOhms	
CompositionMetal FoilFeaturesAutomotive AEC-Q200, Current SenseTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 225°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.035" (0.90mm)Number of Terminations2Failure Rate-	Tolerance	±0.5%	
FeaturesAutomotive AEC-Q200, Current SenseTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 225°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.035" (0.90mm)Number of Terminations2Failure Rate-	Power (Watts)	1W	
Temperature Coefficient±25pm/°COperating Temperature-55°C ~ 225°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.035" (0.90mm)Number of Terminations2Failure Rate-	Composition	Metal Foil	
Operating Temperature -55°C ~ 225°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.035" (0.90mm) Number of Terminations 2 Failure Rate -	Features	Automotive AEC-Q200, Current Sense	
Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.035" (0.90mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±25ppm/°C	
Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.035" (0.90mm) Number of Terminations 2 Failure Rate -	Operating Temperature	-55°C ~ 225°C	
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.035" (0.90mm) Number of Terminations 2 Failure Rate -	Package / Case	1206 (3216 Metric)	
Height - Seated (Max)0.035" (0.90mm)Number of Terminations2Failure Rate-	Supplier Device Package	1206	
Number of Terminations2Failure Rate-	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)	
Failure Rate -	Height - Seated (Max)	0.035" (0.90mm)	
	Number of Terminations	2	
	Failure Rate	-	
Report errors?			Report errors?

CSS1206DT10L0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CSS1206DT10L0 Payment Methods



CSS1206DT10L0 Shipping Methods



If you have any question about CSS1206DT10L0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com