

CSS150-24 Information

Part Number CSS150-24

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 100W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CSS150-24 Specifications

Manufacturer Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series CSS150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation Efficiency 89%	_	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series CSS150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Manufacturer Part Number	CSS150-24
AC DC Converters Package - Series CSS150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Manufacturer	TDK-Lambda Americas Inc.
Package - Series CSS150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Category	Power Supplies - External/Internal (Off-Board)
Series CSS150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Package	
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Series	CSS150
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Voltage - Isolation 4kV (4000V) Efficiency 90 ~ 264 VAC 24V AVA 100W (150W Forced Air) 4.2A 4.2A	Type	Open Frame
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Number of Outputs	1
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Voltage - Output 1	24V
Voltage - Output 4 - Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Voltage - Output 2	-
Current - Output (Max) 4.2A Power (Watts) 100W (150W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Voltage - Output 3	-
Power (Watts) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Voltage - Output 4	
Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 89%	Current - Output (Max)	4.2A
Voltage - Isolation 4kV (4000V) Efficiency 89%	Power (Watts)	100W (150W Forced Air)
Efficiency 89%	Applications	Medical
·	Voltage - Isolation	4kV (4000V)
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	Efficiency	89%
Operating reinperature 0 C - 70 C (With Detailing)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Features DC Input Capable, Remote On/Off, Universal Input	Features	DC Input Capable, Remote On/Off, Universal Input
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Size / Dimension	5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)
Report errors?		Report errors?

CSS150-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CSS150-24 Payment Methods



















CSS150-24 Shipping Methods













If you have any question about CSS150-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com