

CSS50012/T Information

Part Number CSS50012/T

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

AC DC Converters

Description AC/DC CONVERTER 12V 360W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CSS50012/T Specifications

Manufacturer Part Number CSS50012/T Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series CSS500 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 360W (500W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series CSS500 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output (Max) 30A Power (Watts) 360W (500W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Manufacturer Part Number	CSS50012/T
Package - Series CSS500 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 360W (500W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series CSS500 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 360W (500W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Category	Power Supplies - External/Internal (Off-Board)
Series CSS500 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 360W (500W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 360W (500W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Package	-
Number of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)30APower (Watts)360W (500W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency87%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Load Sharing, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Series	CSS500
Voltage - Input90 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)30APower (Watts)360W (500W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency87%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Load Sharing, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Type	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Peatures Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Size / Dimension 12V 12V 12V 12V 12V 12V 12V 12	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Size / Dimension - Current - Output (Max) 30A - Current - Output (Max) 360W (500W Forced Air) - Medical 4kV (4000V) 87% Operating Temperature O°C ~ 70°C (With Derating) Chassis Mount 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Soa A Power (Watts) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Output 4 - Current - Output (Max) Ado 30A Medical 4kV (4000V) Efficiency 87% Operating Temperature O°C ~ 70°C (With Derating) Chassis Mount 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) 30A Power (Watts) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 360W (500W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Voltage - Output 3	-
Power (Watts) 360W (500W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Voltage - Output 4	-
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Current - Output (Max)	30A
Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Power (Watts)	360W (500W Forced Air)
Efficiency 87% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Applications	Medical
Operating Temperature 0°C ~ 70°C (With Derating) Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Efficiency	87%
Mounting Type Chassis Mount Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)	Features	Adjustable Output, Load Sharing, Remote Sense, Standby Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	9.00" L x 4.70" W x 1.63" H (228.6mm x 119.4mm x 41.4mm)
		Report errors?

CSS50012/T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CSS50012/T Payment Methods



















CSS50012/T Shipping Methods













If you have any question about CSS50012/T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com