



CSX-750PDCTR Information



For Reference Only

Part Number CSX-750PDCTR

ManufacturerCitizen Finedevice Co LtdCategoryCrystals, Oscillators, Resonators

Description OSC PROG CMOS 5V STBY 100PPM SMD

Programmable Oscillators

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CSX-750PDCTR Specifications

Manufacturer Part Number CSX-750PDCTR Manufacturer Citizen Finedevice Co Ltd Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series CSX-750P Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 125MHz Function Standby Output CMOS Voltage - Supply 5V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)		
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series CSX-750P Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 125MHz Function Standby Output CMOS Voltage - Supply 5V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Manufacturer Part Number	CSX-750PDCTR
Package 4-SMD, No Lead Series CSX-750P Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 125MHz Function Standby Output CMOS Voltage - Supply 5V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Manufacturer	Citizen Finedevice Co Ltd
Package 4-SMD, No Lead Series CSX-750P Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 125MHz Function Standby Output CMOS Voltage - Supply 5V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Category	Crystals, Oscillators, Resonators
Series CSX-750P Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 125MHz Function Standby Output CMOS Voltage - Supply 5V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)		Programmable Oscillators
Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 125MHz Function Standby Output CMOS Voltage - Supply 5V Frequency Stability + ±100ppm Frequency Stability (Total) - 20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.0276" L x 0.197" W (7.00mm x 5.00mm) Height Max Max	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 125MHz Function Standby Output CMOS Voltage - Supply 5V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 1	Series	CSX-750P
Available Frequency Range Function Standby Output CMOS Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings Asma Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.0276" L x 0.197" W (7.00mm x 5.00mm) Height	Туре	XO (Standard)
Function Standby Output CMOS Voltage - Supply 5V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Programmable Type	Programmed as Request
Output CMOS Voltage - Supply 5V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Available Frequency Range	1MHz ~ 125MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" (1.60mm)	Function	Standby
Frequency Stability (Total)	Output	CMOS
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - 0.063" (1.60mm)	Voltage - Supply	5V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Frequency Stability	±100ppm
Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Frequency Stability (Total)	-
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Current - Supply (Max)	45mA
Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Ratings	-
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.063" (1.60mm)	Mounting Type	Surface Mount
Height 0.063" (1.60mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height	0.063" (1.60mm)
		Report errors?

CSX-750PDCTR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CSX-750PDCTR Payment Methods





















CSX-750PDCTR Shipping Methods













If you have any question about CSX-750PDCTR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com