

# **CUS250LD24**

## **CUS250LD24 Information**

	Part Number Manufacturer Category Description Package	CUS250LD24 TDK-Lambda Americas Inc. Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 24V 250W - For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **CUS250LD24 Specifications**

Manufacturer TDK-Lambda Americas Inc.   Power Supplies - External/Internal (Off-Board) Power Supplies - External/Internal (Off-Board)   Package -   Package CUS250LD   Series CUS250LD   Yope Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 265 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 4 -   Voltage - Output 4 -   Voltage - Soutput 4 -   Voltage - Output 4 -   Voltage - Output 4 -   Voltage - Output 4 -   Voltage - Soutput 4 -   Voltage - Soutput 4 -   Voltage - Soutput 5 -   Voltage - Soutput 6 -   Voltage - Soutput 6 -   Voltage - Soutput 7 -   Voltage - Soutput 6 -   Voltage - Soutput 7 -   Voltage - Soutpu				
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesCUS250LDSperiesOpen FrameNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5StoWaPower (Watts)250WApplicationsITE (Commercial)Voltage - Isolation3kV (300V)Efficiency90%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting Type7.80° L x 4.00° W x 1.18° H (198.0mm x 102.0mm x 30.0mm)	Manufacturer Part Number	CUS250LD24		
AC DC ConvertersPackage-SeriesCUS250LDTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output 4-Current - Output (Max)10.5APower (Watts)250WApplicationsTTE (Commercial)Voltage - Isolation3kV (300V)Efficiency90%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.80° L x 4.00° W x 1.18° H (198.0mm x 102.0mm x 30.0mm)	Manufacturer	TDK-Lambda Americas Inc.		
Package-SeriesCUS250LDTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 40.5ACurrent - Output (Max)10.5APower (Watts)20WVoltage - IsolationTE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting Type7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series CUS250LD   Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 265 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 10.5A   Power (Watts) 250W   Voltage - Isolation 3kV (3000V)   Efficiency 90%   Operating Temperature -25°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.80° L x 4.00° W x 1.18° H (198.0mm x 102.0mm x 30.0mm)		AC DC Converters		
Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 265 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 5 10.5A   Power (Watts) 250W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 90%   Operating Temperature -25°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chasis Mount   Size / Dimension 7.80°L x 4.00°W x 1.18° H (198.0mm x 102.0mm x 30.0mm)	Package	-		
Number of Outputs I   Voltage - Input 85 ~ 265 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 10.5A   Power (Watts) 250W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 90%   Operating Temperature -25°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.80° L x 4.00° W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Series	CUS250LD		
Voltage - Input 85 ~ 265 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 4 -   Current - Output (Max) 10.5A   Power (Watts) 250W   Applications TTE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 90%   Operating Temperature -25°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.80° L x 4.00° W x 1.18° H (198.0mm x 102.0mm x 30.0mm)	Туре	Open Frame		
Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 4 -   Current - Output (Max) 10.5A   Power (Watts) 250W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Operating Temperature -25°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.80° L x 4.00° W x 1.18° H (198.0mm x 102.0mm x 30.0mm)	Number of Outputs	1		
Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 10.5A   Power (Watts) 250W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 90%   Operating Temperature -25°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.80° L x 4.00° W x 1.18° H (198.0mm x 102.0mm x 30.0mm)	Voltage - Input	85 ~ 265 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10.5APower (Watts)250WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Voltage - Output 1	24V		
Voltage - Output 4-Current - Output (Max)10.5APower (Watts)250WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Voltage - Output 2	-		
Current - Output (Max)10.5APower (Watts)250WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Voltage - Output 3	-		
Power (Watts)250WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Current - Output (Max)	10.5A		
Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Power (Watts)	250W		
Efficiency90%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Applications	ITE (Commercial)		
Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Voltage - Isolation	3kV (3000V)		
FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Efficiency	90%		
Mounting Type Chassis Mount   Size / Dimension 7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Operating Temperature	$-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)		
Size / Dimension 7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)	Features	Adjustable Output, DC Input Capable, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	ize / Dimension 7.80" L x 4.00" W x 1.18" H (198.0mm x 102.0mm x 30.0mm)			
			Report errors?	

#### **CUS250LD24 Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **CUS250LD24** Payment Methods





If you have any question about CUS250LD24, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com