

# CW0011K500JE12HS

### **CW0011K500JE12HS Information**



### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## CW0011K500JE12HS Specifications

Manufacturer Part NumberCW0011K500JE12HSManufacturerVishay DaleCategoryResistorsThrough Hole ResistorsThrough Hole ResistorsPackageAxialSeriesCWResistance1.5 kOhmsTolerance±5%Power (Watts)-CompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±30pm/°COperating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device PackageAxialHeight - Seated (Max)-		
CategoryResistorsThrough Hole ResistorsPackageAxialSeriesCWResistance1.5 kOhmsTolerance±5%Power (Watts)-CompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±30pm/°COperating TemperatureAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Manufacturer Part Number	CW0011K500JE12HS
Hough Hole ResistorsPackageAxialSeriesCWResistance1.5 kOhmsTolerance±5%Power (Watts)-CompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingFeatures±30pm/°COperating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Manufacturer	Vishay Dale
PackageAxialPackageCWResistance1.5 kOhmsTolerance±5%Power (Watts)-CompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±30ppm/°COperating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device Package0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Category	Resistors
SeriesCWResistance1.5 kOhmsTolerance±5%Power (Wats)-CompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±30ppm/°COperating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device Package0.094" Dia x 0.406" L (2.39mm x 10.31mm)		Through Hole Resistors
Resistance1.5 kOhmsTolerance±5%Power (Watts)-CompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±30ppm/°COperating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0,094" Dia x 0.406" L (2.39mm x 10.31mm)	Package	Axial
Tolerance±5%Power (Watts)-CompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±30pm/°COperating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Series	CW
Power (Watts)-CompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±30pm/°COperating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Resistance	1.5 kOhms
CompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±30pm/°COperating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Tolerance	$\pm 5\%$
FeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±30pm/°COperating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Power (Watts)	-
Temperature Coefficient±30ppm/°COperating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Composition	Wirewound
Operating Temperature-65°C ~ 350°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Features	Moisture Resistant, Pulse Withstanding
Package / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Temperature Coefficient	±30ppm/°C
Supplier Device PackageAxialSize / Dimension0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Operating Temperature	$-65^{\circ}C \sim 350^{\circ}C$
Size / Dimension 0.094" Dia x 0.406" L (2.39mm x 10.31mm)	Package / Case	Axial
	Supplier Device Package	Axial
Height - Seated (Max)	Size / Dimension	0.094" Dia x 0.406" L (2.39mm x 10.31mm)
	Height - Seated (Max)	-
Number of Terminations 2	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

### CW0011K500JE12HS Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## CW0011K500JE12HS Payment Methods



If you have any question about CW0011K500JE12HS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com