

# CWR-140-20-0203

### CWR-140-20-0203 Information

Containing containing	Part Number Manufacturer Category Description Package	CWR-140-20-0203 CW Industries Connectors, Interconnects Rectangular Connectors - Board In, Direct Wire to Board CONN IDC 20POS W/CVR LIP TIN PCB	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# CWR-140-20-0203 Specifications

ManufacturerCW IndustriesCategoryConnectors, InterconnectsRectangular Connectors - Board In, Direct Wire to BoardPackage-SeriesCWRConnector TypeRibbon CableNumber of Positions0Cable Pitch0.500° (1.27mm)Board-Side Pitch0.200° (5.08mm)Number of Rows4Row Spacing0.100° (2.54mm)Mounting TypeThrough HoleCable Pitch0.503 (Stranded or SolidMounting TypeColosed End, Strain ReliefFeaturesCiosed End, Strain ReliefContact Finish Thickness100µin (2.54µm)		
CategoryConnectors, Interconnects Rectangular Connectors - Board In, Direct Wire to BoardPackage-SeriesCWRConnector TypeRibbon CableNumber of Positions20Cable Pitch0.050° (1.27mm)Board-Side Pitch0.200° (5.08mm)Number of Rows4Row Spacing0.100° (2.54mm)Mounting TypeThrough HoleCable Pitch0.50Wire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact Finish Thickness100µin (2.54µm)ColorBlue	Manufacturer Part Number	CWR-140-20-0203
PackageRectangular Connectors - Board In, Direct Wire to BoardPackage-SeriesCWRConnector TypeRibbon CableNumber of Positions20Cable Pitch0.050" (1.27mm)Board-Side Pitch0.200" (5.08mm)Number of Rows4Row Spacing0.100" (2.54mm)Mounting TypeThrough HoleCable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact Finish Thickness100µin (2.54µm)ColorBlue	Manufacturer	CW Industries
Package-SeriesCWRConnector TypeRibbon CableNumber of Positions20Cable Pitch0.050" (1.27mm)Board-Side Pitch0.200" (5.08mm)Number of Rows4Row Spacing0.100" (2.54mm)Mounting TypeThrough HoleCable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact FinishTinContact Finish ThicknessBlue	Category	Connectors, Interconnects
SeriesCWRConnector TypeRibbon CableNumber of Positions20Cable Pitch0.050" (1.27mm)Board-Side Pitch0.200" (5.08mm)Number of Rows4Row Spacing0.100" (2.54mm)Mounting TypeThrough HoleCable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact FinishTinContact Finish ThicknessBlue		Rectangular Connectors - Board In, Direct Wire to Board
Connector TypeRibbon CableNumber of Positions20Cable Pitch0.050" (1.27mm)Board-Side Pitch0.200" (5.08mm)Number of Rows4Row Spacing0.100" (2.54mm)Mounting TypeThrough HoleCable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact FinishTinContact Finish Thickness100µin (2.54µm)ColorBlue	Package	-
Number of Positions20Cable Pitch0.050" (1.27mm)Board-Side Pitch0.200" (5.08mm)Number of Rows4Row Spacing0.100" (2.54mm)Mounting TypeThrough HoleCable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact FinishTinContact Finish Thickness100µin (2.54µm)ColorBlue	Series	CWR
Cable Pitch0.050" (1.27mm)Board-Side Pitch0.200" (5.08mm)Number of Rows4Row Spacing0.100" (2.54mm)Mounting TypeThrough HoleCable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact FinishTinContact Finish Thickness100µin (2.54µm)ColorBlue	Connector Type	Ribbon Cable
Board-Side Pitch0.200" (5.08mm)Number of Rows4Row Spacing0.100" (2.54mm)Mounting TypeThrough HoleCable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact FinishTinContact Finish Thickness100µin (2.54µm)ColorBlue	Number of Positions	20
Number of Rows4Row Spacing0.100" (2.54mm)Mounting TypeThrough HoleCable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact Finish Thickness100µin (2.54µm)ColorBlue	Cable Pitch	0.050" (1.27mm)
Row Spacing0.100" (2.54mm)Mounting TypeThrough HoleCable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact FinishTinContact Finish Thickness100µin (2.54µm)ColorBlue	Board-Side Pitch	0.200" (5.08mm)
Mounting TypeThrough HoleCable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact FinishTinContact Finish Thickness100µin (2.54µm)ColorBlue	Number of Rows	4
Cable TerminationIDCWire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact FinishTinContact Finish Thickness100µin (2.54µm)ColorBlue	Row Spacing	0.100" (2.54mm)
Wire Gauge28-30 AWG, Stranded or SolidFeaturesClosed End, Strain ReliefContact FinishTinContact Finish Thickness100µin (2.54µm)ColorBlue	Mounting Type	Through Hole
FeaturesClosed End, Strain ReliefContact FinishTinContact Finish Thickness100µin (2.54µm)ColorBlue	Cable Termination	IDC
Contact FinishTinContact Finish Thickness100µin (2.54µm)ColorBlue	Wire Gauge	28-30 AWG, Stranded or Solid
Contact Finish Thickness100µin (2.54µm)ColorBlue	Features	Closed End, Strain Relief
Color Blue	Contact Finish	Tin
	Contact Finish Thickness	100µin (2.54µm)
Report errors?	Color	Blue
		Report errors?

#### CWR-140-20-0203 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## CWR-140-20-0203 Payment Methods



# CWR-140-20-0203 Shipping Methods



If you have any question about CWR-140-20-0203, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com