

CWR-281-37-0000

CWR-281-37-0000 Information



Part Number	CWR-281-37-0000	
Manufacturer	CW Industries	
Category	Connectors, Interconnects D-Sub Connectors	
Description	CONN D-SUB PLUG 37POS STR IDC	
Package	-	
	For the pricing/inventory/lead time, please contact	
	us	
Website: https://www.heisener.com		
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CWR-281-37-0000 Specifications

ManufacturerCW IndustriesCategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesCWRConnector StyleD-SubConnector TypePlug, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FeaturesSeel Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish ThicknessIopin (0.25µm)Ingress Protection-		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesCWRConnector StyleD-SubConnector TypePlug, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FeaturesFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish ThicknessIoµin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	CWR-281-37-0000
D-Sub ConnectorsPackage-SeriesCWRConnector StyleD-SubConnector TypePlug, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FreminationDC, Ribbon CableFeaturesSteel, Tin PlatedShell Material, FinishSteel, Tin PlatedContact Finish ThicknessIojui (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	CW Industries
Package-SeriesCWRConnector StyleD-SubConnector TypePlug, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FreminationDC, Ribbon CableFeaturesSeel, Tin PlatedShell Material, FinishGoldContact Finish ThicknessJojin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesCWRConnector StyleD-SubConnector TypePlug, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)TerminationFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)TerminationDC, Ribbon CableFeaturesFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldIngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesSteel, Tin PlatedShell Material, FinishSteel, Tin PlatedContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	CWR
Number of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish ThicknessIOµin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Female Sockets
Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish ThicknessIoluin (0.25µm)Ingress Protection-Atterial Flammability RatingUL94 V-O	Number of Positions	37
Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	4 (DC, C)
Flange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationIDC, Ribbon CableFeaturesFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Free Hanging (In-Line)
FeaturesFeed Through, Shielded, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	IDC, Ribbon Cable
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Feed Through, Shielded, Strain Relief
Contact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	10µin (0.25µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

CWR-281-37-0000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CWR-281-37-0000 Payment Methods



CWR-281-37-0000 Shipping Methods



If you have any question about CWR-281-37-0000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com