

CWR26HB226MCGCPR

CWR26HB226MCGCPR Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CWR26HB226MCGCPR Specifications

ManufacturerVishay SpragueCategoryCapacitorsTantalum CapacitorsPackage2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance22µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lad Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC(0.01%)		
Category Capacitors Tantalum Capacitors Tantalum Capacitors Package 2711 (6728 Metric) Series Military, MIL-PRF-55365/13, CWR26 Capacitance 22µF Tolerance ±20% Voltage - Rated 15V Type Conformal Coated ESR (Equivalent Series Resistance) 275 mOhm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. - Mounting Type Surface Mount Package / Case 2711 (6728 Metric) Size / Dimension 0.265" L x 0.110" W (6.73mm x 2.79mm) Height - Seated (Max) 0.125" (3.17mm) Lad Spacing - Manufacturer Size Code G Features Military	Manufacturer Part Number	CWR26HB226MCGCPR
Tantalum CapacitorsPackage2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance22μFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265° L x 0.110° W (6.73mm x 2.79mm)Height - Seated (Max)0.125° (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC(0.01%)	Manufacturer	Vishay Sprague
Package2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance22µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC (0.01%)	Category	Capacitors
NumberMilitary, MIL-PRF-55365/13, CWR26Capacitance22μFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.125" (3.17mm)Height - Seated (Max)0.125" (3.17mm)Lad Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC(0.01%)		Tantalum Capacitors
Capacitance22μFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265° L x 0.110° W (6.73mm x 2.79mm)Height - Seated (Max)0.125° (3.17mm)Lad Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC (0.01%)	Package	2711 (6728 Metric)
Tolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-FeaturesGFatures RetC (0.01%)	Series	Military, MIL-PRF-55365/13, CWR26
Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryEatures RateC (0.01%)	Capacitance	22µF
TypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryFeaturesC (0.01%)	Tolerance	$\pm 20\%$
AT275 mOhmESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryC (0.01%)C (0.01%)	Voltage - Rated	15V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC (0.01%)	Туре	Conformal Coated
Lifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC (0.01%)	ESR (Equivalent Series Resistance)	275 mOhm
Mounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC (0.01%)	Operating Temperature	-55°C ~ 125°C
Package / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC (0.01%)	Lifetime @ Temp.	-
Size / Dimension 0.265" L x 0.110" W (6.73mm x 2.79mm) Height - Seated (Max) 0.125" (3.17mm) Lead Spacing - Manufacturer Size Code G Features Military Failure Rate C (0.01%)	Mounting Type	Surface Mount
Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC (0.01%)	Package / Case	2711 (6728 Metric)
Lead Spacing-Manufacturer Size CodeGFeaturesMilitaryFailure RateC (0.01%)	Size / Dimension	0.265" L x 0.110" W (6.73mm x 2.79mm)
Manufacturer Size CodeGFeaturesMilitaryFailure RateC (0.01%)	Height - Seated (Max)	0.125" (3.17mm)
FeaturesMilitaryFailure RateC (0.01%)	Lead Spacing	-
Failure RateC (0.01%)	Manufacturer Size Code	G
	Features	Military
Report errors?	Failure Rate	C (0.01%)
		Report errors?

CWR26HB226MCGCPR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CWR26HB226MCGCPR Payment Methods



If you have any question about CWR26HB226MCGCPR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com