

CWR26HC106KBFATR

CWR26HC106KBFATR Information

Heisener.com	Part Number	CWR26HC106KBFATR
	Manufacturer	Vishay Sprague
	Category	Capacitors Tantalum Capacitors
	Description	CAP TANT 10UF 10% 15V 2214
	Package	2214 (5634 Metric)
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CWR26HC106KBFATR Specifications

Manufacturer Part NumberCWR26HC106KBFATRManufacturerVishay SpragueCategoryCapacitorsPackageZalt (S634 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±10%Voltage - Rated15VSPR (Equivalent Series Resistance)667 mOhmOperating Temperature-Lifetime @ Temp.214 (S634 Metric)Mounting TypeSurface MountSize / Dimension0.220° L x 0.135° W (5.59mm x 3.43mm)Height - Seated (Max)-Manufacturer Size CodeFFaturesMilitaryFaturesBilitarySize / Dimension-Struer Second Matter Size CodeFSecond Matter Size CodeFSecond Matter Size CodeFSecond Matter Size CodeSicondSecond Matter Size CodeFSecond Matter Size CodeSicondSecond Size CodeSicond		
Catagory Capacitors Tantalum Capacitors Tantalum Capacitors Package 2214 (5634 Metric) Series Military, MIL-PRF-55365/13, CWR26 Capacitance 10µF Tolerance ±10% Voltage - Rated 15V Type Conformal Coated ESR (Equivalent Series Resistance) 667 mOhm Operating Temperature -55° C ~ 125°C Lifetime @ Temp. - Mounting Type Surface Mount Package / Case 2214 (5634 Metric) Size / Dimension 0.220° L x 0.135" W (5.59mm x 3.43mm) Height - Seated (Max) 0.085" (2.16mm) Lead Spacing - Features Military Features Military	Manufacturer Part Number	CWR26HC106KBFATR
Tantalum CapacitorsPackage2214 (5634 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±10%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Manufacturer	Vishay Sprague
Package2214 (5634 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±10%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.085" (2.16mm)Height - Seated (Max)0.085" (2.16mm)Lead SpacingFFeaturesMilitaryFailure RateB(0.1%)	Category	Capacitors
ArrowMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±10%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.020" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-FeaturesMilitaryFeaturesB (0.1%)		Tantalum Capacitors
Capacitance10μFTolerance±10%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.020" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryBilitare RateB (0.1%)	Package	2214 (5634 Metric)
Tolerance±10%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.085" (2.16mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-FeaturesMilitaryFeaturesB (0.1%)	Series	Military, MIL-PRF-55365/13, CWR26
Voltage - RatedISWVoltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Capacitance	10µF
TypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Tolerance	±10%
Fraction667 mOhmESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFaulter RateB (0.1%)	Voltage - Rated	15V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Туре	Conformal Coated
Lifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.20" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFaiture RateB (0.1%)	ESR (Equivalent Series Resistance)	667 mOhm
Mounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Operating Temperature	-55°C ~ 125°C
Package / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Lifetime @ Temp.	-
Size / Dimension 0.220" L x 0.135" W (5.59mm x 3.43mm) Height - Seated (Max) 0.085" (2.16mm) Lead Spacing - Manufacturer Size Code F Features Military Failure Rate B (0.1%)	Mounting Type	Surface Mount
Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Package / Case	2214 (5634 Metric)
Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Size / Dimension	0.220" L x 0.135" W (5.59mm x 3.43mm)
Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Height - Seated (Max)	0.085" (2.16mm)
FeaturesMilitaryFailure RateB (0.1%)	Lead Spacing	-
Failure RateB (0.1%)	Manufacturer Size Code	F
	Features	Military
Peport errors?	Failure Rate	B (0.1%)
Report crisis:		Report errors?

CWR26HC106KBFATR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

CWR26HC106KBFATR Payment Methods





CWR26HC106KBFATR Shipping Methods



If you have any question about CWR26HC106KBFATR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com