

CWR26HC226MBGBTR

CWR26HC226MBGBTR Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CWR26HC226MBGBTR Specifications

Manufacturer Part NumberCWR26HC226MBGBTRManufacturerVishay SpragueCategoryCapacitorsPackageTantalun CapacitorsPackage2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance22µFTolerance±20%Voltage - Rated15VSypeConformal CoatedSpraumer-55°C ~ 125°COperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265° L x 0.110° W (6.73mm x 2.79mm)Height - Seated (Max)GMunafacturer Size CodeGFaturesMilitary, MIL-PRE-Size CodeFaturesMilitary, MIL-PRE-Size CodeFaturesMilita		
CategoryCapacitorsPackage2711 (6728 Metric)Package2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance22µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265° L x 0.110° W (6.73mm x 2.79mm)Height - Seated (Max)0.125° (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Manufacturer Part Number	CWR26HC226MBGBTR
Initialum CapacitorsPackage2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance22µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountSize / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead SpacingGFaturesMilitary	Manufacturer	Vishay Sprague
Package2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance22μFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead SpacingGFeaturesMilitaryFeaturesMilitary	Category	Capacitors
SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance22µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead SpacingGFeaturesMilitary		Tantalum Capacitors
Capacitance22μFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265° L x 0.110° W (6.73mm x 2.79mm)Height - Seated (Max)0.125° (3.17mm)Lead SpacingGFeaturesMilitary	Package	2711 (6728 Metric)
Tolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-FeaturesGMunifacturer Size CodeGMilitaryMilitary	Series	Military, MIL-PRF-55365/13, CWR26
Voltage - RatedIstrumeVoltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Capacitance	22µF
TypeConformal CoatedESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Tolerance	±20%
Final275 mOhmESR (Equivalent Series Resistance)275 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Voltage - Rated	15V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Туре	Conformal Coated
Lifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	ESR (Equivalent Series Resistance)	275 mOhm
Mounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Operating Temperature	-55°C ~ 125°C
Package / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Lifetime @ Temp.	-
Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Mounting Type	Surface Mount
Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Package / Case	2711 (6728 Metric)
Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Size / Dimension	0.265" L x 0.110" W (6.73mm x 2.79mm)
Manufacturer Size CodeGFeaturesMilitary	Height - Seated (Max)	0.125" (3.17mm)
Features Military	Lead Spacing	-
•	Manufacturer Size Code	G
Exilume Data $D(0,10/)$	Features	Military
Failure Kate $D(0.1\%)$	Failure Rate	B (0.1%)
Report errors?		Report errors?

CWR26HC226MBGBTR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CWR26HC226MBGBTR Payment Methods



If you have any question about CWR26HC226MBGBTR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com