

CWR26HC336MBFAHR

CWR26HC336MBFAHR Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CWR26HC336MBFAHR Specifications

ManufacturerVishay SpragueCategoryCapacitorsTantalum CapacitorsPackage2214 (5634 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance33µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)800 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220° L x 0.135° W (5.59mm x 3.43mm)Height - Seated (Max)0.085° (2.16mm)Lad Spacing-FeaturesMilitary		
Category Capacitors Tantalum Capacitors Tantalum Capacitors Package 2214 (5634 Metric) Series Military, MIL-PRF-55365/13, CWR26 Capacitance 33µF Tolerance ±20% Voltage - Rated 15V Type Conformal Coated ESR (Equivalent Series Resistance) 800 mOhm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. - Mounting Type Surface Mount Package / Case 2214 (5634 Metric) Size / Dimension 0.220" L x 0.135" W (5.59mm x 3.43mm) Height - Seated (Max) 0.085" (2.16mm) Lad Spacing - Features Military	Manufacturer Part Number	CWR26HC336MBFAHR
Tantalum CapacitorsPackage2214 (5634 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance33μFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)800 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Manufacturer	Vishay Sprague
Package2214 (5634 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance33µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)800 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.085" (2.16mm)Height - Seated (Max)0.085" (2.16mm)Lad SpacingFFeaturesMilitaryFailure RateB (0.1%)	Category	Capacitors
Anilitary, MIL-PRF-55365/13, CWR26Capacitance33µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)800 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.085" (2.16mm)Height - Seated (Max)0.085" (2.16mm)Lad Spacing-FeaturesMilitaryFailure RateB (0.1%)		Tantalum Capacitors
Capacitance33μFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)800 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.085" (2.16mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-FeaturesMilitaryFeaturesB (0.1%)	Package	2214 (5634 Metric)
Tolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)800 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.025" (2.16mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-FeaturesMilitaryBilure RateB (0.1%)	Series	Military, MIL-PRF-55365/13, CWR26
Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)800 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryBilure RateB (0.1%)	Capacitance	33µF
TypeConformal CoatedESR (Equivalent Series Resistance)800 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryBilure RateB (0.1%)	Tolerance	$\pm 20\%$
AT800 mOhmESR (Equivalent Series Resistance)800 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryBilitaryB (0.1%)	Voltage - Rated	15V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryBiller RateB (0.1%)	Туре	Conformal Coated
Lifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryBillitaryB (0.1%)	ESR (Equivalent Series Resistance)	800 mOhm
Mounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Operating Temperature	-55°C ~ 125°C
Package / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Lifetime @ Temp.	-
Size / Dimension 0.220" L x 0.135" W (5.59mm x 3.43mm) Height - Seated (Max) 0.085" (2.16mm) Lead Spacing - Manufacturer Size Code F Features Military Failure Rate B (0.1%)	Mounting Type	Surface Mount
Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Package / Case	2214 (5634 Metric)
Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Size / Dimension	0.220" L x 0.135" W (5.59mm x 3.43mm)
Manufacturer Size CodeFFeaturesMilitaryFailure RateB (0.1%)	Height - Seated (Max)	0.085" (2.16mm)
FeaturesMilitaryFailure RateB (0.1%)	Lead Spacing	-
Failure RateB (0.1%)	Manufacturer Size Code	F
	Features	Military
Report errors?	Failure Rate	B (0.1%)
		Report errors?

CWR26HC336MBFAHR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CWR26HC336MBFAHR Payment Methods



If you have any question about CWR26HC336MBFAHR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com