

# CWR26HH106MCFATR

### **CWR26HH106MCFATR Information**





Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **CWR26HH106MCFATR Specifications**

ManufacturerVishay SpragueCapacitorsTantalum CapacitorsPackage2214 (5634 Metric)Series214 (5634 Metric)Capacitance10µFTolerance20%Voltage - Rated15VTypeConformal CoatedSeries Resistance)667 mOhmOperating Temperature-Voltage / Case214 (5634 Metric)Nounting TypeSurface MountPackage / Case214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateC(0.01%)		
CategoryCapacitorsTantalum CapacitorsPackage2214 (5634 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220° L x 0.135° W (5.59mm x 3.43mm)Height - Seated (Max)0.085° (2.16mm)Lead Spacing-FaturesMilitaryFailure RateC(0.01%)	Manufacturer Part Number	CWR26HH106MCFATR
Tantalum CapacitorsPackage2214 (5634 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220° L x 0.135° W (5.59mm x 3.43mm)Height - Seated (Max)0.085° (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateC(0.01%)	Manufacturer	Vishay Sprague
Package2214 (5634 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.085" (2.16mm)Height - Seated (Max)0.085" (2.16mm)Lad Spacing-Manufacturer Size CodeFFaturesMilitaryFailure RateC(0.01%)	Category	Capacitors
SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.085" (2.16mm)Height - Seated (Max)0.085" (2.16mm)Lad Spacing-FeaturesMilitaryFailure RateC0.01%)		Tantalum Capacitors
Capacitance10μFTolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.085" (2.16mm)Height - Seated (Max)0.085" (2.16mm)Lad Spacing-FaturesMilitaryFaturesC0.01%)	Package	2214 (5634 Metric)
Tolerance±20%Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.025" (2.16mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-FeaturesMilitaryFailure RateC (0.01%)	Series	Military, MIL-PRF-55365/13, CWR26
Voltage - Rated15VTypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryEvaluer RateC (0.01%)	Capacitance	10µF
TypeConformal CoatedESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFeaturesC (0.01%)	Tolerance	±20%
Ar667 mOhmESR (Equivalent Series Resistance)667 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryC (0.01%)C (0.01%)	Voltage - Rated	15V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateC (0.01%)	Туре	Conformal Coated
Lifetime @ TempMounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateC (0.01%)	ESR (Equivalent Series Resistance)	667 mOhm
Mounting TypeSurface MountPackage / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateC (0.01%)	Operating Temperature	-55°C ~ 125°C
Package / Case2214 (5634 Metric)Size / Dimension0.220" L x 0.135" W (5.59mm x 3.43mm)Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateC (0.01%)	Lifetime @ Temp.	-
Size / Dimension 0.220" L x 0.135" W (5.59mm x 3.43mm)   Height - Seated (Max) 0.085" (2.16mm)   Lead Spacing -   Manufacturer Size Code F   Features Military   Failure Rate C (0.01%)	Mounting Type	Surface Mount
Height - Seated (Max)0.085" (2.16mm)Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateC (0.01%)	Package / Case	2214 (5634 Metric)
Lead Spacing-Manufacturer Size CodeFFeaturesMilitaryFailure RateC (0.01%)	Size / Dimension	0.220" L x 0.135" W (5.59mm x 3.43mm)
Manufacturer Size CodeFFeaturesMilitaryFailure RateC (0.01%)	Height - Seated (Max)	0.085" (2.16mm)
FeaturesMilitaryFailure RateC (0.01%)	Lead Spacing	-
Failure RateC (0.01%)	Manufacturer Size Code	F
	Features	Military
Report errors?	Failure Rate	C (0.01%)
Report criois:		Report errors?

### **CWR26HH106MCFATR Guarantees**



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CWR26HH106MCFATR Payment Methods**



If you have any question about CWR26HH106MCFATR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com