

CWR26KK106KBGCTR

CWR26KK106KBGCTR Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CWR26KK106KBGCTR Specifications

Manufacturer Part NumberCWR26KK106KBGCTRManufacturerVishay SpragueCategoryCapacitorsPackageTantalun CapacitorsPackage2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±10%Voltage - Rated25VSyneConformal CoatedSpre350 mOhmOperating Temperature-55°C ~ 125°CMuning TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dinension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)-Lide Spacing-Munafecturer Size CodeGFurseMintyMunafecturer Size CodeGFurseMintyMunafecturer Size CodeGFurseMintyMunafecturer Size CodeGFurseMintyMunafecturer Size CodeGFurseMintyMunafecturer Size CodeGFurseMintyMunafecturer Size CodeGFurseMintyMintyMintyMunafecturer Size CodeMintyFurseMintyMintyMintyMintyMintyMunafecturer Size CodeMintyMunafecturer Size CodeMintyFurseMintyMintyMintyMintyMintyMintyMintyMintyMintyMintyMinty		
CategoryCapacitorsPackage2711 (6728 Metric)Package2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±10%Voltage - Rated25VTypeConformal CoatedESR (Equivalent Series Resistance)350 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265° L x 0.110° W (6.73mm x 2.79mm)Height - Seated (Max)0.125° (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Manufacturer Part Number	CWR26KK106KBGCTR
Initialum CapacitorsPackage2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±10%Voltage - Rated25VTypeConformal CoatedESR (Equivalent Series Resistance)350 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountSize / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead SpacingGFaturesMilitary	Manufacturer	Vishay Sprague
Package2711 (6728 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±10%Voltage - Rated25VTypeConformal CoatedESR (Equivalent Series Resistance)350 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead SpacingGFeaturesMilitaryFeaturesMilitary	Category	Capacitors
SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±10%Voltage - Rated25VTypeConformal CoatedESR (Equivalent Series Resistance)350 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead SpacingGFeaturesMilitary		Tantalum Capacitors
Capacitance10μFTolerance±10%Voltage - Rated25VTypeConformal CoatedESR (Equivalent Series Resistance)350 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265° L x 0.110° W (6.73mm x 2.79mm)Height - Seated (Max)0.125° (3.17mm)Lead SpacingGFeaturesMilitary	Package	2711 (6728 Metric)
Tolerance±10%Voltage - Rated25VTypeConformal CoatedESR (Equivalent Series Resistance)350 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-FeaturesGMunifacturer Size CodeGMilitaryMilitary	Series	Military, MIL-PRF-55365/13, CWR26
Voltage - Rated25VYopeConformal CoatedESR (Equivalent Series Resistance)350 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Capacitance	10µF
TypeConformal CoatedESR (Equivalent Series Resistance)350 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Tolerance	$\pm 10\%$
Final350 mOhmESR (Equivalent Series Resistance)350 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Voltage - Rated	25V
Note-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Туре	Conformal Coated
Lifetime @ TempMounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	ESR (Equivalent Series Resistance)	350 mOhm
Mounting TypeSurface MountPackage / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Operating Temperature	-55°C ~ 125°C
Package / Case2711 (6728 Metric)Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Lifetime @ Temp.	-
Size / Dimension0.265" L x 0.110" W (6.73mm x 2.79mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Mounting Type	Surface Mount
Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Package / Case	2711 (6728 Metric)
Lead Spacing-Manufacturer Size CodeGFeaturesMilitary	Size / Dimension	0.265" L x 0.110" W (6.73mm x 2.79mm)
Manufacturer Size CodeGFeaturesMilitary	Height - Seated (Max)	0.125" (3.17mm)
Features Military	Lead Spacing	-
•	Manufacturer Size Code	G
	Features	Military
Failure Rate B (0.1%)	Failure Rate	B (0.1%)
Report errors?		Report errors?

CWR26KK106KBGCTR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CWR26KK106KBGCTR Payment Methods



If you have any question about CWR26KK106KBGCTR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com