

CWR26MH106JBHCPR

CWR26MH106JBHCPR Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CWR26MH106JBHCPR Specifications

Manufacturer Size CodeHFeaturesMilitary		
CategoryCapacitorsCategoryCapacitorsPackage2915 (7338 Metric)Package2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Manufacturer Part Number	CWR26MH106JBHCPR
Initialum CapacitorsPackage2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountSize / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Manufacturer	Vishay Sprague
Package2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature500 mOhmLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Category	Capacitors
SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-FeaturesMilitary		Tantalum Capacitors
Capacitance10μFTolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-FeaturesMilitary	Package	2915 (7338 Metric)
Tolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-FeaturesMilitary	Series	Military, MIL-PRF-55365/13, CWR26
Voltage - Rated35VYopeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Capacitance	10µF
TypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Tolerance	±5%
Fraction500 mOhmESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Voltage - Rated	35V
Note-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Туре	Conformal Coated
Lifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	ESR (Equivalent Series Resistance)	500 mOhm
Mounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Operating Temperature	-55°C ~ 125°C
Package / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Lifetime @ Temp.	-
Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Mounting Type	Surface Mount
Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Package / Case	2915 (7338 Metric)
Lead Spacing-Manufacturer Size CodeHFeaturesMilitary	Size / Dimension	0.285" L x 0.150" W (7.24mm x 3.81mm)
Manufacturer Size CodeHFeaturesMilitary	Height - Seated (Max)	0.125" (3.17mm)
Features Military	Lead Spacing	-
•	Manufacturer Size Code	Н
	Features	Military
Failure Rate B (0.1%)	Failure Rate	B (0.1%)
Report errors?		Report errors?

CWR26MH106JBHCPR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

CWR26MH106JBHCPR Payment Methods





If you have any question about CWR26MH106JBHCPR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com