

CWR26MH106JCHZPR

CWR26MH106JCHZPR Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CWR26MH106JCHZPR Specifications

Manufacturer Part NumberCWR26MH106JCHZPRManufacturerVishay SpragueCategoryCapacitorsTantalum Capacitors2915 (7338 Metric)Package2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±5%Voltage - Rated35VTypeConformal CoatedSR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempNounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeH		
CategoryCapacitorsCackage2915 (7338 Metric)Package2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountSize / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)	Manufacturer Part Number	CWR26MH106JCHZPR
Tantalum CapacitorsPackage2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ Temp.Surface MountMounting TypeSurface MountSackage / Case2915 (7338 Metric)Size / Dimension0.285° L x 0.150° W (7.24mm x 3.81mm)Height - Seated (Max)0.125° (3.17mm)	Manufacturer	Vishay Sprague
Package2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ Temp.Surface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285° L x 0.150° W (7.24mm x 3.81mm)Height - Seated (Max).125° (3.17mm)	Category	Capacitors
SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max).Lead Spacing.		Tantalum Capacitors
Capacitance10μFTolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)	Package	2915 (7338 Metric)
Tolerance±5%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)	Series	Military, MIL-PRF-55365/13, CWR26
Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)	Capacitance	10µF
TypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-	Tolerance	±5%
Fraction500 mOhmESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-	Voltage - Rated	35V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-	Туре	Conformal Coated
Lifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-	ESR (Equivalent Series Resistance)	500 mOhm
Mounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-	Operating Temperature	-55°C ~ 125°C
Package / Case 2915 (7338 Metric) Size / Dimension 0.285" L x 0.150" W (7.24mm x 3.81mm) Height - Seated (Max) 0.125" (3.17mm) Lead Spacing -	Lifetime @ Temp.	-
Size / Dimension 0.285" L x 0.150" W (7.24mm x 3.81mm) Height - Seated (Max) 0.125" (3.17mm) Lead Spacing -	Mounting Type	Surface Mount
Height - Seated (Max)0.125" (3.17mm)Lead Spacing-	Package / Case	2915 (7338 Metric)
Lead Spacing -	Size / Dimension	0.285" L x 0.150" W (7.24mm x 3.81mm)
	Height - Seated (Max)	0.125" (3.17mm)
Manufacturer Size Code H	Lead Spacing	-
	Manufacturer Size Code	Н
Features Military	Features	Military
Failure RateC (0.01%)	Failure Rate	C (0.01%)
Report errors		Report errors?

CWR26MH106JCHZPR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CWR26MH106JCHZPR Payment Methods





If you have any question about CWR26MH106JCHZPR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com