

# CWR26MH106KBHAHR

# **CWR26MH106KBHAHR Information**





Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **CWR26MH106KBHAHR** Specifications

ManufacturerVishay SpragueCategoryCapacitorsTantalum CapacitorsPackage2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±10%Voltage - Rated35VTypeConformal CoatedSeries Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ Temp.2015 (7338 Metric)Nounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285° L x 0.150° W (7.24mm x 3.81mm)Height - Seated (Max)0.125° (3.17mm)Lad Spacing-FaturesMilitaryFaturesB (0.1%)		
CategoryCapacitorsCategoryTantalum CapacitorsPackage2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±10%Voltage - Rated35VZypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-Lifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)	Manufacturer Part Number	CWR26MH106KBHAHR
Tantalum CapacitorsPackage2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±10%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285° L x 0.150° W (7.24mm x 3.81mm)Height - Seated (Max)0.125° (3.17mm)Lead Spacing-Manufacturer Size CodeHFaturesMilitaryFailure RateB (0.1%)	Manufacturer	Vishay Sprague
Package2915 (7338 Metric)SeriesMilitary, MIL-PRF-55365/13, CWR26Capacitance10µFTolerance±10%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285° L x 0.150° W (7.24mm x 3.81mm)Height - Seated (Max)0.125° (3.17mm)Lead Spacing-Manufacturer Size CodeHFaturesMilitaryFailure RateB (0.1%)	Category	Capacitors
ArrowMilitary, MIL-PRF-55365/13, CWR26Capacitance10μFTolerance±10%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)		Tantalum Capacitors
Capacitance10µFTolerance±10%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.125" (3.17mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFaturesMilitaryFailure RateB (0.1%)	Package	2915 (7338 Metric)
Tolerance±10%Voltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesB (0.1%)	Series	Military, MIL-PRF-55365/13, CWR26
NoticeHereVoltage - Rated35VTypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryBiller RateB (0.1%)	Capacitance	10µF
TypeConformal CoatedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)	Tolerance	$\pm 10\%$
AT500 mOhmESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryB (0.1%)B (0.1%)	Voltage - Rated	35V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)	Туре	Conformal Coated
Lifetime @ TempMounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)	ESR (Equivalent Series Resistance)	500 mOhm
Mounting TypeSurface MountPackage / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)	Operating Temperature	-55°C ~ 125°C
Package / Case2915 (7338 Metric)Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)	Lifetime @ Temp.	-
Size / Dimension0.285" L x 0.150" W (7.24mm x 3.81mm)Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)	Mounting Type	Surface Mount
Height - Seated (Max)0.125" (3.17mm)Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)	Package / Case	2915 (7338 Metric)
Lead Spacing-Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)	Size / Dimension	0.285" L x 0.150" W (7.24mm x 3.81mm)
Manufacturer Size CodeHFeaturesMilitaryFailure RateB (0.1%)	Height - Seated (Max)	0.125" (3.17mm)
FeaturesMilitaryFailure RateB (0.1%)	Lead Spacing	-
Failure RateB (0.1%)	Manufacturer Size Code	Н
	Features	Military
	Failure Rate	B (0.1%)
Report errors?		Report errors?

# **CWR26MH106KBHAHR** Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CWR26MH106KBHAHR Payment Methods**



If you have any question about CWR26MH106KBHAHR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com