

CY8C4245AZI-M445

CY8C4245AZI-M445 Information

	Embedded - Microcontrollers ion IC MCU 32BIT 32KB FLASH 64TQFP 64-LQFP For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CY8C4245AZI-M445 Specifications

Manufacturer Part NumberCY8C4245AZI-M445ManufacturerCypress Semiconductor CorpCategoryIntegrated Circuits (ICs)Package64-LQFPSeriesPSOC® 4 CY8C42x - MCore ProcessorARM® Cortex®-M0Core Size32-BitSpeed48MHzConnectivityPC, IrDA, LINbus, Microwire, SmartCard, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, Cap Sense, LCD, LVD, POR, PWM, SmartSense, WDTNumber of I/O51Program Memory Size32KB (32K x 8)EEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1,71 v ~ 5.5 VData ConvertersA/D 8x12b
CategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage64-LQFPSeriesPSOC® 4 CY8C42xx - MCore ProcessorARM® Cortex®-M0Core Size32-BitSpeed48MHzConnectivityFC, IrDA, LINbus, Microwire, SmartCard, SPI, SSP, UART/USARTPeripheralsBrown-out Detect/Reset, Cap Sense, LCD, LVD, POR, PWM, SmartSense, WDTNumber of I/O51Program Memory Size32KB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V~5.5 V
Imbeddef - Microcontrollers Package 64-LQFP Series PSOC® 4 CY8C42xx - M Core Processor ARM® Cortex®-M0 Core Size 32-Bit Speed 48MHz Connectivity PC, IrDA, LINbus, Microwire, SmartCard, SPI, SSP, UART/USART Peripherals Brown-out Detect/Reset, Cap Sense, LCD, LVD, POR, PWM, SmartSense, WDT Number of I/O 51 Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 4K x 8 Voltage - Supply (Vcc/Vdd) 1.71 V~55 V
Package64-LQFPSeriesPSOC® 4 CY8C42xx - MCore ProcessorARM® Cortex®-M0Core Size32-BitSpeed48MHzConnectivityFC, IrDA, LINbus, Microwire, SmartCard, SPI, SSP, UART/USARTPeripheralsBrown-out Detect/Reset, Cap Sense, LCD, LVD, POR, PWM, SmartSense, WDTNumber of I/O51Program Memory SizeSZKB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM SizeMX x 8Voltage - Supply (Vcc/Vdd)1.71 V~5.5 V
SeriesPSOC® 4 CY8C42xx - MCore ProcessorARM® Cortex®-M0Core Size32-BitSpeed48MHzConnectivityPC, IrDA, LINbus, Microwire, SmartCard, SPI, SSP, UART/USARTPeripheralsBrown-out Detect/Reset, Cap Sense, LCD, LVD, POR, PWM, SmartSense, WDTNumber of I/O51Program Memory Size32KB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V ~ 5.5 V
Core ProcessorARM® Cortex®-M0Core Size32-BitSpeed48MHzConnectivityPC, IrDA, LINbus, Microwire, SmartCard, SPI, SSP, UART/USARTPeripheralsBrown-out Detect/Reset, Cap Sense, LCD, LVD, POR, PWM, SmartSense, WDTNumber of I/O51Program Memory Size32KB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V~5.5 V
Core Size32-BitSpeed48MHzConnectivityFC, IrDA, LINbus, Microwire, SmartCard, SPI, VART/USARTPeripheralsBrown-out Detect/Reset, Cap Sense, LCD, LVD, POR, PWM, SmartSense, WDTNumber of I/O51Program Memory Size32KB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vd)1.71 V~5.5 V
Speed48MHzConnectivityPC, IrDA, LINbus, Microwire, SmartCard, SPI, SSP, UART/USARTPeripheralsBrown-out Detect/Reset, Cap Sense, LCD, LVD, POR, PWM, SmartSense, WDTNumber of I/O51Program Memory Size32KB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V~5.5 V
PeripherPeripheralsPC, IrDA, LINbus, Microwire, SmartCard, SPI, SSP, UART/USARTPeripheralsBrown-out Detect/Reset, Cap Sense, LCD, LVD, POR, PWM, SmartSense, WDTNumber of I/O51Program Memory Size32KB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V~5.5 V
PeripheralsBrown-out Detect/Reset, Cap Sense, LCD, LVD, POR, PWM, SmartSense, WDTNumber of I/O51Program Memory Size32KB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V ~ 5.5 V
Number of I/O51Program Memory Size32KB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V ~ 5.5 V
Program Memory Size32KB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V ~ 5.5 V
Program Memory TypeFLASHEEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V ~ 5.5 V
EEPROM Size-RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V ~ 5.5 V
RAM Size4K x 8Voltage - Supply (Vcc/Vdd)1.71 V ~ 5.5 V
Voltage - Supply (Vcc/Vdd) 1.71 V ~ 5.5 V
Data ConvertersA/D 8x12b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ (TA)
Mounting Type -
Package / Case 64-LQFP
Supplier Device Package64-TQFP (10x10)
Report er

CY8C4245AZI-M445 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

CY8C4245AZI-M445 Payment Methods



CY8C4245AZI-M445 Shipping Methods



If you have any question about CY8C4245AZI-M445, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com