

## D09P13B6GX00LF

Quote

### **D09P13B6GX00LF Information**

Heisener.com	Part Number	D09P13B6GX00LF	
	Manufacturer	Amphenol FCI	in Nord
	Category	Connectors, Interconnects D-Sub Connectors	
	Description	CONN D-SUB PLUG 9POS R/A SOLDER	
	Package	-	- 1944 A
		For the pricing/inventory/lead time, please contact	E123-5
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## D09P13B6GX00LF Specifications

Manufacturer     Amphenol FCI       Connectors, Interconnects     D-Sub Connectors       Package     -       Series     Delta D       Connector Style     Delta D       Connector Style     Delta D       Connector Style     Plug, Male Pins       Number of Positions     9       Shell Size, Connector Layout     1(DE, E)       Contact Type     Signal       Mounting Type     Housing/Shell (4-40)       Flange Feature     Soder       Features     Soder Connector Signal       Shell Material, Finish     Steel, Tin Plated       Contact Finish Thickness     Gold or Gold, GXT?       Contact Finish Thickness     Supin (0.76µm)		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeFluosing/Shell (4-40)Flange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µi (0.76µm)Ingerse ProtectionJuly 4V-0	Manufacturer Part Number	D09P13B6GX00LF
D-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessJufu 24 V-0	Manufacturer	Amphenol FCI
Package-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Contact Finish ThicknessJUE Y-O	Category	Connectors, Interconnects
SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Contact Finish ThicknessJupin (0.76µm)Ingress Protection-Waterial Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleHousing/Shell (4-40)SolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Waterial Flammability RatingUL94 V-0	Series	Delta D
Number of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleHousing/Shell (4-40)SolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	9
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeaturesHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish ThicknessJupin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (4-40)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	1 (DE, E)
Flange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Grounding Indents, Mounting Brackets
Contact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection -   Material Flammability Rating UL94 V-0	Contact Finish	Gold or Gold, GXT?
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30µin (0.76µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

#### **D09P13B6GX00LF Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## D09P13B6GX00LF Payment Methods



## D09P13B6GX00LF Shipping Methods



If you have any question about D09P13B6GX00LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com