

D09P33E6GL00LF

D09P33E6GL00LF Information

Heisener.com	 D09P33E6GL00LF Amphenol FCI Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 9POS R/A SOLDER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D09P33E6GL00LF Specifications

Manufacturer Amphenol FCI Canectors, Interconnects D-Sub Connectors Package - Series Delta D Connector Style D-Sub Connectors Connector Style Pulug, Male Pins Connector Style 9 Number of Positions 9 Steries, Connector Layout 1 (DE, E) Contact Type Signal Mounting Type Through Hole, Right Angle Packares Solder Features Board Lock, Grounding Indents, Mounting Brackets Shell Material, Finish Steel, Tin Plated Contact Finish Thickness Ojuin (0.76µm) Appendict Finish Thickness UL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeFhrough Hole, Right AngleParininationSolderFerminationSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Auterial Flammability RatingUL94 V-0	Manufacturer Part Number	D09P33E6GL00LF
D-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsConnector Type9Number of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMuuning TypeThrough Hole, Right AnglePlange FeatureHousing/Shell (M3)FerminationSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessSipul (M2)Muterial Flammability RatingUL94 V-0	Manufacturer	Amphenol FCI
Package-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMunting TypeThrough Hole, Right AnglePlange FeatureHousing/Shell (M3)FerminationSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessOjuni (OrGul, GXT?Contact Finish ThicknessJUE Y-OMaterial Flammability RatingUL94 V-O	Category	Connectors, Interconnects
SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AnglePlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishStel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Contact Finish ThicknessJujui (0.76µm)Auterial Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AnglePlange FeatureBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Contact Finish ThicknessJujin (0.76µm)Muterial Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleHousing/Shell (M3)SolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	Delta D
Number of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AnglePlange FeatureHousing/Shell (M3)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Contact Finish ThicknessJupin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGold or Gold, GXT?Contact Finish ThicknessJupin (0.76µm)Augeral Flammability RatingUL94 V-0	Number of Positions	9
Contact TypeSignalMounting TypeThrough Hole, Right AngleFange FeaturesHousing/Shell (M3)FeaturesSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish ThicknessJuin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	1 (DE, E)
Flange FeatureHousing/Shell (M3)FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
FerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (M3)
Shell Material, FinishSteel, Tin PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Grounding Indents, Mounting Brackets
Contact Finish Thickness 30µin (0.76µm) Ingress Protection - Material Flammability Rating UL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold or Gold, GXT?
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30µin (0.76µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

D09P33E6GL00LF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D09P33E6GL00LF Payment Methods



D09P33E6GL00LF Shipping Methods



If you have any question about D09P33E6GL00LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com