



### D09S80C6GV00 Information

Heisener.com

Part Number D09S80C6GV00 Manufacturer Amphenol FCI

Category Connectors, Interconnects

**D-Sub Connectors** 

**Description** CONN DSUB RCPT 9POS R/A PRESSFIT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## D09S80C6GV00 Specifications

Manufacturer Part NumberD09880C6GV00ManufacturerAmphenol FCICategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)FerminationPress-FitFeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	î de la companya de	
Category Connectors, Interconnects D-Sub Connectors  Package - Series Delta D Connector Style D-Sub Connector Type Receptacle, Female Sockets Number of Positions 9 Number of Rows 2 Shell Size, Connector Layout Contact Type Signal Mounting Type Through Hole, Right Angle Flange Feature Mating Side, Female Screwlock (4-40) Termination Press-Fit Features Board Guide Shell Material, Finish Steel, Tin Plated Contact Finish Contact Finish Contact Finish Thickness Signin Outley Old Contact Finish Thickness Tingles Through Hole, Right Angle Contact Finish Thickness Through Hole, Right Angle Contact Finish Steel, Tin Plated Contact Finish Contact Finish Thickness Through Hole, Right Angle Contact Finish Thickness Through Hole, Right Angle Contact Finish Steel, Tin Plated Contact Finish Thickness Through Hole, Right Angle T	Manufacturer Part Number	D09S80C6GV00
Package-SeriesDelta DConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol FCI
Package-SeriesDelta DConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesDelta DConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector Type Receptacle, Female Sockets  Number of Positions 9  Number of Rows 2  Shell Size, Connector Layout 1 (DE, E)  Contact Type Signal  Mounting Type Through Hole, Right Angle  Flange Feature Mating Side, Female Screwlock (4-40)  Termination Press-Fit  Features Board Guide  Shell Material, Finish Steel, Tin Plated  Contact Finish Thickness 30µin (0.76µm)  Ingress Protection -  Material Flammability Rating UL94 V-0	Series	Delta D
Number of Positions  Number of Rows  2  Shell Size, Connector Layout  1 (DE, E)  Contact Type  Signal  Mounting Type  Through Hole, Right Angle  Flange Feature  Mating Side, Female Screwlock (4-40)  Termination  Press-Fit  Features  Board Guide  Shell Material, Finish  Steel, Tin Plated  Contact Finish  Gold  Contact Finish Thickness  30µin (0.76µm)  Ingress Protection  Material Flammability Rating  UL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	9
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	1 (DE, E)
Flange FeatureMating Side, Female Screwlock (4-40)TerminationPress-FitFeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
Termination Press-Fit Features Board Guide Shell Material, Finish Steel, Tin Plated Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Ingress Protection - Material Flammability Rating UL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard GuideShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Mating Side, Female Screwlock (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Press-Fit
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Guide
Contact Finish Thickness 30μin (0.76μm)  Ingress Protection -  Material Flammability Rating UL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection - Material Flammability Rating UL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30μin (0.76μm)
1 - 1	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

#### D09S80C6GV00 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### D09S80C6GV00 Payment Methods



















## D09S80C6GV00 Shipping Methods













If you have any question about D09S80C6GV00, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com