



D0Z18G63 Information

Heisener.com

Part NumberD0Z18G63ManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 63A 380VAC/250VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D0Z18G63 Specifications

Manufacturer Part Number DOZ18G63 Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series - Fuse Type Cartridge Current Rating 63A Voltage Rating - AC 380V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features Indicating Class D0 Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.591" Dia x 1.417" L (15.00mm x 36.00mm)			
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeries-Fuse TypeCartridgeCurrent Rating63AVoltage Rating - AC380VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassD0ApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Manufacturer Part Number	D0Z18G63	
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeries-Fuse TypeCartridgeCurrent Rating63AVoltage Rating - AC380VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassD0ApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Manufacturer	Littelfuse Inc.	
PackageCartridge, Non-StandardSeries-Fuse TypeCartridgeCurrent Rating63AVoltage Rating - AC380VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassD0ApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Category	Circuit Protection	
Series-Fuse TypeCartridgeCurrent Rating63AVoltage Rating - AC380VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassD0ApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.591" Dia x 1.417" L (15.00mm x 36.00mm)		Electrical, Specialty Fuses	
Fuse TypeCartridgeCurrent Rating63AVoltage Rating - AC380VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassD0ApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Package	Cartridge, Non-Standard	
Current Rating Voltage Rating - AC 380V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features Indicating Class D0 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 63A 840 840 840 840 840 840 840 84	Series	-	
Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features Indicating Class D0 Approvals VDE Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 380V 380V 380V 380V 250V 400 400 400 400 400 400 400	Fuse Type	Cartridge	
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features Indicating Class D0 Approvals VDE Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V	Current Rating	63A	
Response Time Applications Electrical, Industrial Features Indicating Class D0 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial Feature Indicating Foot Size / Dimension Fast Fast Fast Fast Fast Fast Fast Fast	Voltage Rating - AC	380V	
Applications Electrical, Industrial Features Indicating Class D0 Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Voltage Rating - DC	250V	
Features Indicating Class D0 Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Response Time	Fast	
Class D0 Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Applications	Electrical, Industrial	
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension VDE - Cartridge, Non-Standard 0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Features	Indicating	
Operating Temperature Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Class	D0	
Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Approvals	VDE	
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Operating Temperature	-	
Package / Case Cartridge, Non-Standard Size / Dimension 0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Breaking Capacity @ Rated Voltage	50kA	
Size / Dimension 0.591" Dia x 1.417" L (15.00mm x 36.00mm)	Mounting Type	Holder	
	Package / Case	Cartridge, Non-Standard	
D	Size / Dimension	0.591" Dia x 1.417" L (15.00mm x 36.00mm)	
Report errors?		Report error	rs?

D0Z18G63 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D0Z18G63 Payment Methods





















D0Z18G63 Shipping Methods













If you have any question about D0Z18G63, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com