

D15P33E6RL12LF

D15P33E6RL12LF Information

Heisener.com	 D15P33E6RL12LF Amphenol FCI Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 15POS R/A - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



D15P33E6RL12LF Specifications

Manufacturer Amphenol FCI Connectors, Interconnects D-Sub Connectors Package - Series Delta D Connector Style Delta D Connector Style Plug, Male Pins Connector Type Plug, Male Pins Number of Positions 15 Shell Size, Connector Layout 2 (DA, A) Contact Type Signal Mounting Type Through Hole, Right Angle Flange Feature Board Guide, Grounding Indents, Mounting Brackets Shell Material, Finish Steel, Nickel Plated Contact Finish Thickness Gold or Gold, GXT? Ingress Protection -		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolder PasteFeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	D15P33E6RL12LF
D-Sub ConnectorsPackage-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)FeaturesSolder PasteShell Material, FinishSteel, Nickel PlatedContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessUL94 V-0	Manufacturer	Amphenol FCI
Package-SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessGold or Gold, GXT?Contact Finish ThicknessJuju (0.76µm)Muterial Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesDelta DConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureBoard Guide, Grounding Indents, Mounting BracketsFeaturesSolder PasteShell Material, FinishSteel, Nickel PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolder PasteFeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)TerminationSolder PasteFeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Waterial Flammability RatingUL94 V-0	Series	Delta D
Number of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)TerminationSolder PasteFeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)TerminationSolder PasteFeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)TerminationSolder PasteFeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessGold or Gold, GXT?Contact Finish ThicknessJupin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	15
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeaturesHousing/Shell (M3)TerminationSolder PasteFeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-VL94 V-0UL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureHousing/Shell (M3)TerminationSolder PasteFeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureHousing/Shell (M3)TerminationSolder PasteFeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolder PasteFeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Guide, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (M3)
Shell Material, FinishSteel, Nickel PlatedContact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder Paste
Contact FinishGold or Gold, GXT?Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Guide, Grounding Indents, Mounting Brackets
Contact Finish Thickness30μin (0.76μm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Nickel Plated
Ingress Protection - Material Flammability Rating UL94 V-0	Contact Finish	Gold or Gold, GXT?
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30µin (0.76µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

D15P33E6RL12LF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

D15P33E6RL12LF Payment Methods



D15P33E6RL12LF Shipping Methods



If you have any question about D15P33E6RL12LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com