



D22018LH Information



For Reference Only

Part Number D22018LH
Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D22018LH Specifications

Manufacturer Part Number D22018LH Manufacturer NKK Switches Category Switches Package - Series D2 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Locking Lever Actuator Length 19.40mm Illumination Non-Illuminated Illumination Voltage (Nominal) - Mounting Type, Color Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features - Report errors?		
Category Package Package Circuit SPDT Switch Function Mom-Off-Mom Current Rating O.4VA (AC/DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Actuator Length Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Trough Hole, Right Angle Termination Style Panel Cutout Dimensions - Bushing Thread Ingress Protection Features - Spd. Actuator Toggle Switches 102 Actuator Actuator Amom-Off-Mom Mom-Off-Mom Adva (AC/DC) 48V Actuator Acy Actuator Average Aver	Manufacturer Part Number	D22018LH
Package - Series D2 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Locking Lever Actuator Length 19.40mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Monuting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features - Incompleted Incomplete Incomp	Manufacturer	NKK Switches
Package-SeriesD2CircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC48VVoltage Rating - DC48VActuator TypeLocking LeverActuator Length19.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-Features-	Category	Switches
Series D2 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Locking Lever Actuator Length 19.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features -		Toggle Switches
CircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC48VVoltage Rating - DC48VActuator TypeLocking LeverActuator Length19.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-Features-	Package	-
Switch Function Mom-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Locking Lever Actuator Length 19.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Features Mom-Off-Mom Mom-Off-Mom Andom-Off-Mom And	Series	D2
Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Locking Lever Actuator Length 19.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features - O.4VA (AC/DC) 48V Actualor Cube (Nominal) 48V Actualor Lever 48V	Circuit	SPDT
Voltage Rating - AC48VVoltage Rating - DC48VActuator TypeLocking LeverActuator Length19.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-Features-	Switch Function	Mom-Off-Mom
Voltage Rating - DC Actuator Type Locking Lever Actuator Length 19.40mm Illumination Non-Illuminated Illumination Type, Color	Current Rating	0.4VA (AC/DC)
Actuator Type Locking Lever Actuator Length 19.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features - Locking Lever Locking Lever 19.40mm Non-Illumination Pon-Illuminated Unthreaded Locking Lever 19.40mm Non-Illuminated Unthreaded Locking Lever Ingress Potection - Locking Lever - Locking Lever Ingress Potection - Locking Lever Ingress Potection - Locking Lever Ingress Potection - Locking Lever - Locking L	Voltage Rating - AC	48V
Actuator Length 19.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Features 19.40mm Non-Illuminated Luminated Unthreaded Ingress Protection Features 19.40mm Non-Illuminated Luminated Unthreaded Ingress Protection Features 19.40mm Non-Illuminated Luminated Unthreaded Ingress Protection Features 19.40mm Non-Illuminated Luminated Ingress Protection Features 19.40mm Non-Illuminated Luminated Ingress Protection Features 19.40mm Non-Illuminated Luminated Ingress Protection Features 19.40mm Non-Illuminated Luminated 19.40mm Luminate	Voltage Rating - DC	48V
Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions Bushing Thread Unthreaded Ingress Protection Features Features Non-Illuminated Unthreaded Non-Illuminated Unthreaded Non-Illuminated Unthreaded Features	Actuator Type	Locking Lever
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-Features-	Actuator Length	19.40mm
Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features - - - - - - - - - - - - -	Illumination	Non-Illuminated
Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Through Hole, Right Angle PC Pin PC Pin	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Unthreaded Bushing Thread Unthreaded Ingress Protection	Mounting Type	Through Hole, Right Angle
Bushing Thread Unthreaded Ingress Protection Features	Termination Style	PC Pin
Ingress Protection - Features -	Panel Cutout Dimensions	-
Features -	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

D22018LH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D22018LH Payment Methods





















D22018LH Shipping Methods













If you have any question about D22018LH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com