

D22018P Information



For Reference Only

Part Number D22018P
Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 48V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D22018P Specifications

Manufacturer Part Number D22018P Manufacturer NKK Switches Category Switches Package - Series D2 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features -		
Category Switches Package - Series D2 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features -	Manufacturer Part Number	D22018P
Package - Series D2 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features -	Manufacturer	NKK Switches
Package - Series D2 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features -	Category	Switches
Series D2 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features -		Toggle Switches
CircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC48VVoltage Rating - DC48VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-Features-	Package	-
Switch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC48VVoltage Rating - DC48VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-Features-	Series	D2
Current Rating 0.4VA (AC/DC) Voltage Rating - AC 48V Voltage Rating - DC 48V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features -	Circuit	SPDT
Voltage Rating - AC48VVoltage Rating - DC48VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-Features-	Switch Function	Mom-Off-Mom
Voltage Rating - DC48VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-Features-	Current Rating	0.4VA (AC/DC)
Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features Standard Round 10.50mm Non-Illuminated - Circular - 6.50mm Dia M6 x 0.75 - Features Standard Round 10.50mm Non-Illuminated - Actuator Length Non-Illuminated - Illuminated - Illuminated - Illumination Type, Color - Illuminated - Illuminated	Voltage Rating - AC	48V
Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features Features Indicator 10.50mm 10.50mm Circular - 6.50mm Dia M6 x 0.75 Features Features Ingress Protection Features Ingress Protection Ingress Prote	Voltage Rating - DC	48V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-Features-	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection Features - - - - - - - - - - - - -	Actuator Length	10.50mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-Features-	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread M6 x 0.75 Ingress Protection Features Circular - 6.50mm Dia M6 x 0.75	Mounting Type	Panel Mount
Bushing Thread M6 x 0.75 Ingress Protection - Features -	Termination Style	PC Pin
Ingress Protection - Features -	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features -	Bushing Thread	M6 x 0.75
	Ingress Protection	-
Report errors?	Features	-
Report cross.		Report errors?

D22018P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

D22018P Payment Methods



















D22018P Shipping Methods













If you have any question about D22018P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com